

NORTHWEST CORNER SECTION 23, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 453 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 5"** FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS EAST TO THE 20" X 11" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-16-12
 - 2) 79.90 CHAINS EAST TO THE 24" X 10" X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-16-12

- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 74 DATED NOVEMBER 20, 1883 FOR A ROAD IN TOWNSHIP 16, RANGE 12 FOR H. Y. WILBUR, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 23-16-12 ON THE FIRST ROAD OF THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-16-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THIS 60 FOOT WIDE ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-16-12 TO END THE FIRST ROAD ON THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 249 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 582 TO 584 PETITIONED BY B. H. Y. WILBUR AND OTHERS FOR TWO ROADS IN TOWNSHIP 16-12[PACKET 495 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 20, 1883, WAS ESTABLISHED AS 40 FOOT AND 60 FOOT WIDE ROADS ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 31, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-16-12 ON THE FIRST ROAD ON THIS ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS FIRST 60 FOOT WIDE ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-16-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THIS FIRST 60 FOOT WIDE ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-16-12 AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY

- 4) STATE HIGHWAY COMMISSION SURVEYORS H. L. OAKES, J. L. DOLE AND JOHN REID, FOR PROJECT 50N-29-FAP 419 "F" IN JUNE 1929, SAID ON PAGE 27 OF THEIR FIELD NOTES THAT **THEY SET A 1/2" IRON PIPE** FOR THE NORTHWEST CORNER OF SECTION 23-16-12. THEY SAID "THIS CORNER WAS RELOCATED BY EXTENDING LINE BETWEEN THE NORTHEAST CORNER OF SECTION 23-16-12 AND THE NORTH 1/4 CORNER SECTION STONE OF SAID SECTION 23-16-12 AT 2,642.5' WEST OF SAID 1/4 SECTION STONE; 2,642.5' BEING ALSO THE MEASURED DISTANCE BETWEEN SAID NORTHEAST CORNER STONE AND NORTH 1/4 SECTION STONE".
 - 1) 3.95' LEFT [SOUTH] OF STATION 647+19.0
 - 2) 58.7' NORTH TO A 1/2" IRON PIPE
 - 3) 62.0' SSW TO A 1/2" IRON PIPE
 - 4) 52.2' SSW TO A 1/2" IRON PIPE

NORTHWEST CORNER SECTION 23-16-12