

CENTER 1/4 CORNER SECTION 26, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 74 UPON NOTICE FROM J. W. DAVIDSON REQUIRING HIM TO LOCATE THE CENTER CORNER OF SECTION 26-16-12, HE OWNING THE NORTHWEST 1/4 OF SAID SECTION 26 AND HIS OTHER CORNERS BEING IN AND THE LOCATION OF THE CENTER CORNER BEING IN DOUBT, SAID THAT **HE SET A 12" X 8" X 15" STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 26-16-12 ON TRUE LINE AND EQUIDISTANT BETWEEN THE QUARTER STONE THAT HE FOUND AT THE WEST SIDE OF SECTION 26-16-12 AND THE QUARTER STONE THAT HE FOUND ON THE EAST SIDE OF SECTION 26-16-12 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE ON JUNE 1, 1910 AND ENTERED ON DECEMBER 22, 1910.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,649' WEST TO THE QUARTER STONE HE FOUND ON THE WEST SIDE OF SECTION 26-16-12
 - 2) 2,649' EAST TO THE QUARTER STONE HE FOUND ON THE EAST SIDE OF SECTION 26-16-12

- 2) RICHARD L. MATTSO, L.S. 1447 OF MIDLAND SURVEYING, INC., IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 4, 2011 FOR PROJECT NUMBER 83621510010GG, A PLAT OF EASEMENT SURVEY FOR THE NATURAL RESOURCES CONSERVATION SERVICE, LARGE SURVEY SR #26002 IN THE SURVEY DRAWER, SAID THAT **HE SET A 5/8" IRON BAR AND ALUMINUM "CLS 176" CAP** AT THE MIDPOINT BETWEEN THE EAST 1/4 CORNER OF SECTION 26-16-12 AND THE WEST 1/4 CORNER OF SECTION 26-16-12. HE NOTED THAT A PERMANENT SURVEY BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, DATED 12/1910 ESTABLISHED THE CENTER CORNER OF SECTION 16-16-12 AT THIS MID-POINT AS RECORDED IN [PERMANENT] SURVEY BOOK 1 ON PAGE 74. HORIZONTAL TIES:
 - 1) 8.2' EAST TO A SET NAIL & SHINER IN A HEDGE FENCE POST
 - 2) 18.05' SE TO A SET NAIL & SHINER IN A HEDGE FENCE POST
 - 3) 15.80' NE TO A SET NAIL & SHINER IN A HEDGE FENCE POST
 - 4) 25.95' WSW TO A SET 30 D NAIL & SHINER IN A 10" TREEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640.45' WEST TO THE 5/8" REBAR WITH HIS ALUMINUM "CLS 176" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 26-16-12 [YINGLING = 2,649.00']
 - 2) 2,640.45' EAST TO THE 5/8" REBAR WITH HIS ALUMINUM "CLS 176" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 26-16-12 [YINGLING = 2,649.00']
 - 3) 2,638.12' NORTH TO THE 5/8" CAPPED REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 26-16-12
 - 4) 2,638.00' SOUTH TO THE THEORETICAL LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 26-16-12 AS WITNESSED BY THE 5/8" REBAR WITH HIS ALUMINUM "CLS 176" CAP HE SET AT 50.00' EAST

CENTER CORNER 26-16-12