

WEST 1/4 CORNER SECTION 29, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 464 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-16-12.
- 2) REA BOOK 30 ON PAGE 22 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 29-16-12 ON APRIL 29, 1939 AT 2,660.5 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 29-16-12. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' EAST TO A WITNESS PIN
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-12 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 SECTION 29-16-12". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' EAST TO A WITNESS
- 4) MARTIN G. LONG, L.S. 1081, OF CP ENGINEERS AND LAND SURVEYORS, IN A LAND SURVEY REFERENCE REPORT DATED JULY 01, 1998, FOR JOB NUMBER 98-145, SAID THAT **HE FOUND A 1/2" SQUARE REBAR AT 1.2 FEET DEEP AT THE WEST 1/4 CORNER OF SECTION 29-16-12. HE SET A 1/2" REBAR WITH CORPORATION LS-27 CAP TO 0.2 DEEP.**
 - 1) 25.90 EAST TO A SPIKE & WASHER IN A CORNER FENCE POST
 - 2) 32.63 SE TO A SPIKE & WASHER IN A GATE POST
 - 3) 24.77 WEST TO A SPIKE & WASHER IN A STUB POLE

WEST QUARTER CORNER 29-16-12