

**WEST 1/4 CORNER SECTION 30, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 82 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 13" X 6"** FOR THE WEST 1/4 CORNER OF SECTION 30-16-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 18, 1856.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-16-12
  - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-16-12
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 97, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 177 DATED JUNE 28, 1904 BY THE ORDER OF T. G. WISDOM FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF SECTION 24-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 25-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY** AS HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-16-11 TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-16-11. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 60 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 158" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER SECTION 30-16-12