

NORTHWEST CORNER SECTION 31, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 81 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 5"** FOR THE CORNER TO SECTIONS 30 & 31-16-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 18, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 33.00 CHAINS EAST TO THE 13" X 9" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-16-12
- 2) 73.00 CHAINS EAST TO THE 16" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-16-12
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 19" X 12" X 6" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-16-12
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 19" X 8" X 5" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 11 & 12 EAST AT THE SOUTHWEST CORNER OF SECTION 31-16-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 136 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 130 TO 132 PETITIONED BY L. WRIGHT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-11 AND 16-12 [PACKET 374 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 12, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-16-12 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 228 DATED SEPTEMBER 12, 1881, FOR A ROAD SURVEY IN TOWNSHIPS 16-11 & 16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-16-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 134 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 122 TO 124 PETITION BY C. H. HIBBEN AND OTHERS FOR A COUNTY ROAD ON THE RANGE LINE BETWEEN RANGES 11 & 12 BETWEEN TOWNSHIPS 16 & 17 [PACKET 89 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 15, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY

COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-18-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 226 DATED SEPTEMBER 15, 1881, FOR A ROAD SURVEY IN TOWNSHIPS 16 & 17 IN RANGES 11 & 12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

3) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 130 & 131 FOR ROAD NUMBER 136 BY A PETITION BY JOHN C. WHEELER [PACKET 374 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED SEPTEMBER 1881, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.

7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY

2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THEN CONTINUES EAST ON THE SECTION LINES FROM THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 29-16-13 TO THE STONE HE FOUND ON THE EAST LINE OF LYON COUNTY AT THE SOUTHEAST CORNER OF SECTION 27-16-13 TO END THIS ROAD SURVEY

8) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 8 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 9) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 155 DATED DECEMBER 6 & 7, 1886 FOR A ROAD IN TOWNSHIP 16-11 FOR D. L. SAYLOR, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE TO END THE FIRST ROAD ON THIS ROAD SURVEY ON THE RANGE LINE.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 12-16-11 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) **NOTE:** SEE ROAD RECORD BOOK "C" ON PAGE 372 – THE ROAD WAS GRANTED FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12 – THE BALANCE OF THE ROAD WAS **REJECTED** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- 10) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 355 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 370 TO 372 PETITIONED BY D. L. SAYLORS AND OTHERS COMMENCING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-16-12, THENCE SOUTH OVER A ROAD ALREADY LOCATED TO THE SOUTHEAST CORNER OF SECTION 12-17-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-17-11 [PACKET 604 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 6, 1886, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE. ON JANUARY 5, 1887 THE BOARD OF COUNTY COMMISSIONERS GRANTED THE ROAD FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12, AND THE BALANCE OF THE ROAD WAS **REJECTED** AS NOTED BY T. E. McMILLAN, CHAIRMAN, AND RECORDED ON JANUARY 18, 1887 BY ROLAND LAKIN, COUNTY CLERK.
- 11) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHEAST CORNER OF

SECTION 36-16-11 AS HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-16-12 TO THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-16-11 ON THIS **PERMANENT SURVEY**.

- 12) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 97, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 177 DATED JUNE 28, 1904 BY THE ORDER OF T. G. WISDOM FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF SECTION 24-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 60 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 158" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 79.94 CHAINS NORTH ON THE RANGE LINE TO THE STONE MARKED "R" HE FOUND AND **HE ACCEPTED** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 24-16-11
- 2) 119.98 CHAINS NORTH ON THE RANGE LINE TO THE ORIGINAL GOVERNMENT STONE HE FOUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 24-16-11
- 3) 160.02 CHAINS NORTH ON THE RANGE LINE TO THE 15" X 9" X 3" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 24-16-11
- 4) 200.06 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-16-11 AT 20 FEET WEST OF A FENCE

- 13) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 118, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 199 DATED JANUARY 3, 1905 FOR TWO ROADS ON THE RANGE LINE BETWEEN TOWNSHIP 16, RANGES 11 & 12 FOR J. A. RABOURN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE TO END THE SECOND ROAD APPROVED ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE SECOND ROAD APPROVED ON THIS ROAD SURVEY EXTENDS NORTH ON THE RANGE LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-12 TO BEGIN THE SECOND ROAD APPROVED ON THIS ROAD SURVEY

- 14) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 598 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 261 THROUGH 264 PETITION BY J. A. RABOURN AND OTHERS FOR A ROAD ON THE RANGE LINE BETWEEN TOWNSHIPS 16-11 AND 16-12 AS FOLLOWS: BEGINNING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH ON THE SECTION LINE OR AS NEAR AS PRACTICABLE 4 MILES TO THE SOUTHEAST CORNER OF SECTION 25-16-11 AND THERE ENDING [PACKET 748 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 3, 1905, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE TO END THE SECOND ROAD APPROVED ON THIS ROAD SURVEY. THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS GRANTED THE NORTH MILE AND THE SOUTH MILE **ONLY** AT 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS SURVEYED, ON APRIL 6, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON MAY 9, 1905 BY ALVA J. SMITH,

COUNTY SURVEYOR. THE REMAINDER OF THE ROAD AS PETITIONED WAS **REJECTED.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 2) THE SECOND ROAD APPROVED ON THIS ROAD SURVEY EXTENDS NORTH ON THE RANGE LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-12 TO BEGIN THE SECOND ROAD APPROVED ON THIS ROAD SURVEY

- 15) REA BOOK 30 ON PAGES 20.5 & 21 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTHWEST CORNER OF SECTION 31-16-12 ON THE RANGE LINE IN THE CENTER OF THE ROAD [APPROXIMATELY] EAST AND WEST. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS IRON PIN AS IT WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 22' NE TO EAST GUARD WALL OF CULVERT
 - 2) 22.25' NW TO WEST GUARD WALL
 - 3) 38' SE TO A WITNESS PIN 1' WEST OF HEDGE AND 5' SOUTH OF CORNER OF HEDGE STUMPS
 - 4) 34' SW TO A WITNESS PIN 8" SOUTHEAST OF A CORNER FENCE POST

- 16) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-11 SHOWS AN **IRON PIN** AT THE "SE CORNER SECTION 25-16-11" ON THE RANGE LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 38' SE TO A WITNESS
 - 2) 34' SW TO A WITNESS

- 17) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 74

ON JANUARY 22, 1951 A PETITION SIGNED BY T. H. JOHNSON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-12 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND R. W. BALL, COUNTY ENGINEER, ON FEBRUARY 23, 1951 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 2, 1951 **VACATED** THE FOLLOWING ROAD:

 - 1) BEGINNING ON THE SOUTHEAST CORNER OF SECTION 30-16-12, THENCE WEST ONE MILE AND TERMINATING AT THE SOUTHWEST CORNER OF SECTION 30-16-12.

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SURVEY FILED IN VOLUME 451, PAGE 759 IN THE REGISTER OF DEEDS OFFICE, FOR PROJECT NUMBER 90055, DATED MARCH 21, 1990, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE. **HE FOUND A SQUARE 5/8" REBAR** ON THE RANGE LINE FROM AN AI CHAMNESS REA SURVEY. **HE ACCEPTED** THIS SQUARE 5/8" REBAR AS IT WAS IN A REASONABLE POSITION FOR THE SOUTHEAST CORNER OF SECTION 25-16-11.
 - 1) 2,649.78' WEST TO THE SOUTH 1/4 CORNER OF SECTION 25-16-11
 - 2) 49.9' ENE TO A NAIL & WASHER IN A CORNER POST
 - 3) 39.0' NW TO A NAIL & WASHER IN A POST
 - 4) 33.2' SW TO A NAIL & WASHER IN A POWER POLE
 - 5) 56.5' SE TO A NAIL & WASHER IN A GATE POST
 - 6) 3.0' EAST TO THE CENTERLINE TRAVELED WAY NORTH-SOUTH
 - 7) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY TO THE WEST

CONTINUED ON PAGE 6

- 19) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 14, 1992, FOR CULVERT REPLACEMENT PROJECT NUMBER 92-P2, **FOUND THE 5/8" SQUARE IRON BAR** AT THE NORTHWEST CORNER OF SECTION 31-16-12 ON THE RANGE LINE FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED MARCH 1990.
- 1) 49.1' ENE TO A FOUND NAIL & WASHER IN A CORNER FENCE POST
 - 2) 38.6' NW TO A FOUND NAIL & WASHER IN A FENCE POST
 - 3) 32.9' SW TO A FOUND NAIL & WASHER IN A POWER POLE
 - 4) 55.8' SE TO A FOUND NAIL & WASHER IN A GATE POST
 - 5) 3' EAST TO THE TRAVELED WAY OF COUNTY ROAD "N" TO THE SOUTH
 - 6) 3' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 260 TO THE WEST
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 2008, FOR PROJECT NUMBER 07415-02, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY OF TWO TRACTS IN THE SOUTHWEST 1/4 OF SECTION 36-16-11 FOR MARK & TAMMY DENTON, SAID THAT **HE FOUND THE 5/8" SQUARE REBAR** AT THE NORTHEAST CORNER OF SECTION 36-16-11 ON THE RANGE LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 1990.
- 1) 49.10' ENE TO A NAIL & WASHER IN A CORNER FENCE POST
 - 2) 40.00' NW TO A CONCRETE NAIL & WASHER IN A DEADMAN POLE
 - 3) 46.30' SE TO A CONCRETE NAIL & WASHER IN A DEADMAN POLE
 - 4) 32.90' SW TO A NAIL & WASHER IN A POWER POLE
 - 5) 1.5' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "N" TO THE SOUTH
 - 6) 3.00' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 260 TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,648.38' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 36-16-11
 - 2) 5,269.36' WEST TO THE 5/8" REBAR THROUGH THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 36-16-11
 - 3) 2,652.53' SOUTH ON THE RANGE LINE TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 36-16-11
 - 4) 5,287.44' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-16-11 ON THE TOWNSHIP LINE

NORTHWEST CORNER SECTION 31-16-12