

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 463 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 11" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.98 CHAINS WEST TO THE 16" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-16-12
 - 2) 39.97 CHAINS EAST TO THE 24" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-16-12

- 2) REA BOOK 30 ON PAGE 22 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 32-16-12 AT 2,647 FEET EAST OF THE NORTHWEST CORNER OF SECTION 3216-12. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' NORTH TO A WITNESS PIN

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-12 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 29-16-12". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' NORTH TO A WITNESS [REA]

- 4) MARTIN G. LONG, L.S. 1081, OF CP ENGINEERS AND LAND SURVEYORS, IN A LAND SURVEY REFERENCE REPORT DATED JULY 1, 1998, FOR JOB NUMBER 98-145 E, SAID THAT **HE FOUND A 5/8" SQUARE REBAR AT 0.25 FEET DEEP** AT THE SOUTH 1/4 CORNER OF SECTION 29-16-12.
 - 1) 20.53' NORTH TO A SPIKE & WASHER IN THE TOP OF A CORNER FENCE POST
 - 2) 37.61' NW TO A SPIKE & WASHER IN THE TOP OF A BRACE POST
 - 3) 31.73' SSE TO A SPIKE & WASHER IN THE TOP OF A BRACE POST
 - 4) 4.0' SOUTH TO THE TRAVELED WAY OF THE EAST-WEST GRAVEL ROAD

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 23, 2013 FOR PROJECT NUMBER 13016, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, THE SURVEY OF A 9.87 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 32-16-12 FOR CAROL J. CURLESS, SAID THAT **HE FOUND A 3/4" SQUARE IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 32-16-12 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE BY MARTIN LONG, L.S. 1081, DATED 1998.
 - 1) 37.95 WNW TO A SPIKE & WASHER IN THE TOP OF A BRACE POST
 - 2) 20.5' NORTH TO A SPIKE & WASHER IN THE TOP OF A CORNER FENCE POST
 - 3) 31.5' SSE TO A SPIKE & WASHER IN THE TOP OF A TIE POST
 - 4) IN LINE WITH A FENCE TO THE NORTH
 - 5) 5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 320 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,865.07' EAST TO THE SOUTHWEST CORNER OF THE 9.87 ACRE TRACT AS WITNESSED BY THE 1/2" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET AT 25.00 FEET NORTH
 - 2) 2,640.07' EAST TO THE 5/8" SQUARE IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-16-12

NORTH QUARTER CORNER 32-16-12