

NORTHWEST CORNER SECTION 32, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 463 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 10" X 4"** FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.98 CHAINS EAST TO THE 12" X 11" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-16-12
 - 2) 79.95 CHAINS EAST TO THE 24" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-16-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 29 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 114 TO 116 PETITIONED BY JAMES JONES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AND 17-12 [PACKET 124 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON JULY 10, 1879, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 12, 1879, AND RECORDED ON JULY 16, 1879, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 30-16-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO A POINT 295 FEET NORTH OF THE SOUTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 20-16-12 AT A TURN TO THE NORTHEASTERLY DUE TO HILL CREEK
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-17-12 AT A TURN TO THE WEST ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 166 BUT DATED JULY 10, 1879, FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AND 17-12, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 20-16-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO AN ANGLE POINT 295' NORTH OF THE SOUTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 20-16-12
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-17-12

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 136 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 130 TO 132 PETITIONED BY L. WRIGHT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-11 AND 16-12 [PACKET 374 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 12, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNT CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 31-16-12 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE NORTHWEST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 228 DATED SEPTEMBER 12, 1881, FOR A ROAD SURVEY IN TOWNSHIPS 16-11 & 16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 31-16-12 TO END THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 30-16-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY
2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12, AND THEN CONTINUES EAST ON THE SECTION LINES FROM THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 29-16-13 TO THE STONE HE FOUND ON THE EAST LINE OF LYON COUNTY AT THE SOUTHEAST CORNER OF SECTION 27-16-13 TO END THIS ROAD SURVEY
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPT ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 30-16-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 9 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.

- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 122, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 203 DATED APRIL 18, 1905 AT THE ORDER OF S. L. WHITMORE FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF SECTION 6-17-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE BROKEN STONE AT 34 LINKS SOUTH AND 25 LINKS EAST OF A CORNER POST** AT THE NORTHEAST CORNER OF SECTION 31-16-11 ON THIS **PERMANENT SURVEY**. HE NOTED: "BY RETRACING THE SURVEY MADE BY M. BROWN IN 1886, I FOUND THAT HIS CHAIN RAN 26 LINKS LONG TO THE 1/2 MILE". HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 168 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 26" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 118.27 CHAINS SOUTH TO THE 20" X 9" X 5" STONE HE MARKED "+" ON THE WEST SIDE HE SET FOR PERMANENT EAST 1/4 CORNER OF SECTION 6-17-12
 - 2) 158.42 CHAINS SOUTH TO THE ORIGINAL STONE HE FOUND LOOSE ON THE GROUND AND **HE RESET** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 6-17-12 ON THE TOWNSHIP LINE
 - 3) 238.71 CHAINS SOUTH TO THE GOVERNMENT STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-12 AT 36 LINKS EAST AND 22 LINKS SOUTH OF THE CORNER OF A HEDGE
- 8) REA BOOK 30 ON PAGE 22 SAYS THAT **THEY SET AN IRON PIN** FOR THE "NE CORNER SECTION 31-16-12" IN THE CENTER OF THE INTERSECTION AT 5,299.7 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 31. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 49' NW TO A WITNESS PIN 16" WEST OF A CORNER FENCE POST
 - 2) 29' NE TO A WITNESS PIN
 - 3) 29' NW TO A WITNESS PIN
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-12 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 29-16-12": **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 29' NE AND 29' NW TO A WITNESS [REA]
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 74
ON JANUARY 22, 1951 A PETITION SIGNED BY T. H. JOHNSON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-12 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND R. W. BALL, COUNTY ENGINEER, ON FEBRUARY 23, 1951 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 2, 1951 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING ON THE SOUTHEAST CORNER OF SECTION 30-16-12, THENCE WEST ONE MILE AND TERMINATING AT THE SOUTHWEST CORNER OF SECTION 30-16-12.

NORTHWEST CORNER 32-16-12