

NORTH 1/4 CORNER SECTION 33, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 460 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 11" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-16-12, FROM WHICH:
 - 1) A HACKBERRY TREE 20" IN DIAMETER BEARS N. 12° W. AT 5 LINKS DISTANCE
 - 2) A HACKBERRY TREE 25" IN DIAMETER BEARS N. 82° E. AT 39 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 40.05 CHAINS WEST TO THE 24" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 29, 32 & 33-16-12
 - 2) 40.05 CHAINS EAST TO THE 24" X 9" X 9" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 12 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 67 DATED MARCH 24, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS TO THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-16-12 ON THIS **PERMANENT SURVEY**. HE MARKED NEW **WITNESS TREES** AS FOLLOWS:
 - 1) A 15" DIAMETER MULBERRY TREE BEARS N. 2°25' W. AT 19 FEET DISTANCE
 - 2) AN 18" DIAMETER ELM TREE BEARS S. 62°35' E. AT 22 FEET DISTANCE

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

 - 1) 1,312-1/2' WEST TO THE POST HE SET FOR THE TEMPORARY NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 33-16-12
 - 2) 2,625' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-16-12

NORTH QUARTER CORNER 33-16-12