

**WEST 1/4 CORNER SECTION 33, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 459 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 10" X 8"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-16-12.
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 12 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 67 DATED MARCH 24, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS TO THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-16-12, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 33-16-12 ON THIS PERMANENT SURVEY.**  
**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**
  - 1) 1,333' EAST TO THE 20" X 10" X 8" STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 33-16-12
  - 2) 2,666' EAST TO THE 15" X 14" X 2" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 33-16-12

WEST QUARTER CORNER 33-16-12