

CENTER CORNER SECTION 34, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 211 DATED MAY 16-22, 1878, ORDERED BY LYMAN BETTS AND OTHERS TO SUBDIVIDE SECTION 34-16-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 34-16-12 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNER ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS, 0.1 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 34-16-12
 - 2) 160 RODS, 0.2 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 34-16-12
 - 3) 80 RODS, 0.3 LINKS NORTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 34-16-12
 - 4) 160 RODS, 0.7 LINKS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 34-16-12
 - 5) 79 RODS, 13.7 LINKS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 34-16-12
 - 6) 159 RODS, 2-1/2 LINKS EAST TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 34-16-12
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 30 TO 31 FOR ROAD NUMBER 8 BY A PETITION BY T. E. BEST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-12 [PACKET 102 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 21, 1878, WAS APPROVED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1878, AND WAS RECORDED ON DECEMBER 2, 1878 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE CENTER CORNER OF SECTION 34-16-12 AT A TURN ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE 1/4 SECTION LINE FOR 2,640' TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 34-16-12 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST FOR 25'; THEN CONTINUES SOUTH PARALLEL WITH THE 1/4 SECTION LINE FOR 135 RODS AT A TURN TO THE LEFT FOR 25' TO RETURN TO THE SECTION LINE; THEN CONTINUES SOUTH ON THE 1/4 SECTION LINE FOR 330' TO A TURN TO THE SOUTHWESTERLY

CENTER CORNER 34-16-12