

**NORTH 1/4 CORNER SECTION 36, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 447 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-16-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.08 CHAINS WEST TO THE 22" X 8" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-16-12
  - 2) 40.08 CHAINS EAST TO THE 24" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36 ON THE EAST TOWNSHIP BOUNDARY
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 25, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 25 DATED APRIL 6, 1870 TO ESTABLISH THE CENTER OF SECTION 36-16-12 AND THE CENTER OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 AND TO SUBDIVIDE THE 1/4'S INTO 40 ACRE LOTS, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 36-16-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 36-16-12
- 2) 2,640' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 36-16-12
- 3) 3,960' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 36-16-12
- 4) 5,280' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 36-16-12 ON THE TOWNSHIP LINE
- 5) 1,315-1/2 WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 36-16-12
- 6) 2,631' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-16-12

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 36-16-12 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.99 CHAINS EAST TO THE WIRE FENCE RUNNING SOUTH SAID TO HAVE BEEN SET WHILE THE STONE WAS IN PLACE AT THE LOCATION FOR THE NORTHWEST CORNER OF SECTION 31-16-13 ON THE RANGE LINE
- 2) 83.84 CHAINS EAST TO THE STONE HE FOUND ON THE INDIAN RESERVE LINE ON THE NORTH SIDE OF THE NE1/4 OF SECTION 31-16-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 120.04 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 31-16-13
- 4) 140.08 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 32-16-13
- 5) 160.12 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-16-13
- 6) 200.20 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 33-16-13
- 7) 240.23 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-16-13
- 8) 279.27 CHAINS EAST TO THE STONE FOUND AT THE NORTHEAST CORNER OF SECTION 33-16-13

NORTH QUARTER CORNER 36-16-12