

**WEST 1/16 CORNER OF THE SOUTHWEST QUARTER OF SECTION 03, TOWNSHIP 16 SOUTH, RANGE 13 EAST**

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 214 DATED JUNE 3 & 4, 1878 ORDERED BY L. JOHNSON & OTHERS FOR A SURVEY OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 3-16-13, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 3-16-13 ON LINE AND AT THE MIDWAY POINT BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-16-13 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-16-13 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 79 RODS, 19 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-16-13
  - 2) 79 RODS, 19 LINKS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-16-13
  - 3) 159 RODS, 19 LINKS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 3-16-13
  
- 2) JOHN E. TAYLOR, L.S. 713, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 16, 1985, FOR JOB NUMBER 449, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 16-13 AT THE REQUEST OF THE PRODUCTION CREDIT ASSOCIATION BY JEFF VAN HORN TO ESTABLISH THE NORTH LINE OF THE SOUTH 1/2 OF THE OF THE SOUTHEAST 1/4 OF SECTION 3-16-13, SAID THAT HE DUG WITH A COUNTY BACKHOE FOR THE STONE AT THE WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-16-13, BUT HE DID **NOT** THE STONE. HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-16-13 TO BE ON LINE AND HALF WAY BETWEEN THE LIMESTONES THAT HE FOUND AT THE SOUTHWEST CORNER AND THE WEST 1/4 CORNER OF SECTION 3-16-13, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.  
HIS SURVEY SHOWED THE FOLLOWING INFORMATION:
  - 1) 1,317.72' NORTH TO THE LIMESTONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-16-13, WITH A 1/2" DIAMETER IRON BAR WITH HIS "LS 713" CAP HE SET OVER THE TOP OF THE LIMESTONE
  - 2) 1,317.72' SOUTH TO THE LIMESTONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-16-13, WITH A 1/2" DIAMETER IRON BAR WITH HIS "LS 713" CAP HE SET OVER THE TOP OF THE STONE

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 03-16-13