

NORTH 1/4 CORNER OF SECTION 07, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 615 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 6"** FOR THIS CORNER AT 40.00 CHAINS EAST OF THE NORTHWEST CORNER OF SECTION 7-16-13 ON THE RANGE LINE. THEY SAID THAT AT 47.04 CHAINS EAST OF THE NORTHWEST CORNER OF SECTION 7-16-13 THEY INTERSECTED THE WEST BOUNDARY OF THE SAC & FOX LANDS AT 21.16 CHAINS NORTH OF A STONE SET ON SAID LINE AND 78.40 CHAINS SOUTH OF THE INTERSECTION OF THE SAC & FOX LINE WITH THE 3RD STANDARD PARALLEL ON FEBRUARY 4TH, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 6, 7 & 12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 7.04 CHAINS EAST TO THE 18" X 16" X 4" LIMESTONE MARKED "CC" THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX INDIAN LANDS
 - 3) 40.04 CHAINS EAST TO THE 18' X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-13
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 175 DATED OCTOBER 8, 1879, FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AND 16-13, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 6-16-13 FOR THE END OF THIS ROAD SURVEY.

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 54 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 218 TO 220 PETITIONED BY LEVI SMITH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AD 16-13 [PACKET 135 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 6, 1879, WAS ESTABLISHED AS A 40 FEET WIDE ROAD ON JANUARY 7, 1880, AND WAS RECORDED ON JANUARY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 6-16-13 FOR THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO A POINT 2,132' WEST OF THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 6-16-13 AT A TURN TO THE SOUTHWESTERLY DUE TO ELM CREEK; THEN INTERSECTS THE SECTION LINE AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 1-16-12; THEN CONTINUES WEST ON THE SECTION LINES FOR 2,640' TO THE SOUTHWEST CORNER OF SECTION 1-16-12 TO COMMENCE THIS ROAD SURVEY
- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 25.5 SAYS THAT **THEY BEGAN THIS SURVEY AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12, BUT THEY RAN 2,648.5' SOUTH TO SET THE CENTER OF SECTION 7-16-13, MAKING THE STARTING POINT THE SOUTH 1/4 CORNER OF SECTION 6-16-13.**
 - 5) REA BOOK 30 ON PAGE 51 SAYS THAT **THEY DROVE A REA IRON PIN** IN THE CENTER OF THE ROAD AND 1,328 FEET EAST OF THE WEST 1/2/4 CORNER ON THE SOUTH LINE OF SECTION 6-16-13 FOR THIS CORNER. **MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 30' SOUTH TO A WITNESS PIN DRIVEN IN THE HEDGE ON THE SOUTH SIDE OF

THE ROAD

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 7, 2002, FOR PROJECT NUMBER 02452-02, SAID THAT HE DUG WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 7-16-13, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**, AND HE DID **NOT** REESTABLISH THE NORTH 1/4 CORNER OF SECTION 7-16-13 AT THIS TIME.

NORTH QUARTER CORNER 07-16-13