

NORTH 1/4 CORNER SECTION 08, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 614 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-16-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 18" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-13
 - 2) 40.00 CHAINS EAST TO THE 18" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-13

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 11 DATED MAY 31, 1882 FOR A ROAD IN TOWNSHIP 16-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-16-13 ON THIS ROAD SURVEY, AND THE CENTERLINE OF THIS ROAD SURVEY FELL **10 FEET NORTH** OF THIS STONE. HE NOTED THAT THE WIDTH WAS ORDERED TO BE 60 FEET.
HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,652 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-16-13; THEN CONTINUED WEST ON THE SECTION LINES FOR 2,192 FEET TO THE STONE HE FOUND ON THE WEST BOUNDARY OF THE SAC & FOX TRUST LANDS AT THE SOUTHEAST CORNER OF LOT 4 ON THE SOUTH SIDE OF SECTION 6-16-13 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,650 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-16-13; THEN CONTINUES EAST ON THE SECTION LINES FOR 2,651 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-16-13; THEN CONTINUES EAST ON THE SECTION LINES FOR 2,640 FEET TO THE STONE HE SET FOR THE NORTHEAST CORNER OF SECTION 9-16-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD 179 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 302 TO 304 PETITION BY JOHN M. WILBUR AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-13 [PACKET 427 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1882, WAS ESTABLISHED AS A 60 FOOT ROAD ON JULY 11, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF 8-16-13 THIS ROAD SURVEY.
HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,652 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-16-13; THEN CONTINUED WEST ON THE SECTION LINES FOR 2,192 FEET TO THE STONE HE FOUND ON THE WEST BOUNDARY OF THE SAC & FOX TRUST LANDS AT THE SOUTHEAST CORNER OF LOT 4 ON THE SOUTH SIDE OF SECTION 6-16-13 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,650 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-16-13; THEN CONTINUES EAST ON THE SECTION LINES FOR 2,651 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-16-13; THEN CONTINUES EAST ON THE SECTION LINES FOR 2,640 FEET TO THE STONE HE SET FOR THE NORTHEAST CORNER OF SECTION 9-16-13 AT THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) REA BOOK 30 ON PAGE 25.5 SAYS THAT **THEY DROVE AN IRON PIN** IN LINE WITH FENCES TO THE NORTH AND SOUTH AT 2,648.5 FEET EAST OF THE SOUTHEAST CORNER OF SECTION 6-16-13 FOR THE SOUTH 1/4 CORNER OF SECTION 5-16-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 22' NORTH TO A WITNESS PIN BY A FENCE POST
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 05-16-13". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 22' NORTH TO A WITNESS [REA]
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 3, 2000, FOR JOB NUMBER 99703-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-13 TO SURVEY THE NORTH HALF AND THE SOUTH HALF OF THE SOUTHEAST 1/4 OF SECTION 5-16-13 AND THE SOUTH 300 FEET OF THE EAST 1,320 FEET OF SECTION 5-16-13 AND THE NORTH 330 FEET OF THE EAST 1,320 FEET OF SECTION 8-16-13, SAID THAT **HE FOUND A SQUARE 5/8" BENT REBAR** FROM AN AI CHAMNESS REA SURVEY AT THE SOUTH 1/4 CORNER OF SECTION 5-16-13. HE EXCAVATED FOR THE STONE AT THIS CORNER, BUT THE STONE WAS **NOT** FOUND IN THE DIRT ROAD. HE ACCEPTED THE REBAR'S POSITION FOR THE SECTION CORNER. **HE REPLACED THE FOUND BENT SQUARE REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 5-16-13.
- 1) 23.4' NORTH TO A CONCRETE NAIL & BOTTLE CAP IN A POST
- 2) IN LINE WITH A TREE LINE TO NORTH
- 3) 80.8' WNW TO A SPIKE & WASHER IN A 40" ELM TREE
- 4) 3' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 360 TO THE EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,320.00' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SE1/4 OF SECTION 5-16-13
- 2) 2,640.00' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 5-16-13
- 3) 1,327.88' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A PROPERTY CORNER
- 4) 2,647.88' EAST TO THE BROKEN GLO STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-16-13 THAT **HE REPLACED** WITH A 5/8" REBAR WITH A LYON COUNTY CAP

NORTH QUARTER CORNER 08-16-13