

NORTH 1/4 CORNER OF SECTION 27, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 602 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 8" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-16-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-16-13
 - 2) 40.00 CHAINS EAST TO THE 18" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-16-13 ON THE COUNTY LINE

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 48, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 48 DATED AUGUST 4, 1884 PER THE AGREEMENT OF T. GALUTIA, A. G. GALUTIA, A. R. GALUTIA, GEORGE W. KIBBE, Y. ALBION DAVIDSON AND ANDREW DAVIDSON TO SUBDIVIDE SECTION 27-16-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 27-16-13 ON THIS **AGREEMENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,983' SOUTH TO THE STONE HE SET FOR AN AGREEMENT CORNER
 - 2) 2,644' SOUTH TO THE STONE HE SET FOR THE CENTER CORNER OF SEC. 27-16-13
 - 3) 3,636' SOUTH TO THE STONE HE SET FOR AN AGREEMENT CORNER
 - 4) 3,967' SOUTH TO THE STONE SET FOR THE WEST 1/4/4 CORNER OF THE SE1/4 OF SECTION 27-16-13
 - 5) 5,290' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 27-16-13

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTH 1/4 CORNER OF SECTION 22-16-13 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.11 CHAINS WEST TO THE LOCATION FOR THE NORTHWEST CORNER OF SECTION 27-16-13
 - 2) 120.13 CHAINS WEST TO THE ORIGINAL GOVERNMENT STONE HE FOUND ON THE GROUND AND **HE RESET** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 20-16-13
 - 3) 160.24 CHAINS WEST TO THE LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 20-16-13
 - 4) 200.35 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 21-16-13, AT 30 LINKS SOUTH OF A FENCE
 - 5) 237.13 CHAINS WEST TO THE LOCATION FOR THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 19-16-13, AT 30 FEET WEST OF A HEDGE

HIS INFORMATION IS CONTINUED ON PAGE 2

- 6) 241.78 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-16-13
- 7) 281.90 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-16-13 ON THE RANGE LINE, IN THE CENTER OF THE ROAD

NORTH QUARTER CORNER 27-16-13