

**NORTH 1/4 CORNER OF SECTION 30, TOWNSHIP 16 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 611 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-16-13 AT 40.00 CHAINS EAST OF THE NORTHWEST CORNER OF SECTION 30-19-13 ON THE WEST TOWNSHIP BOUNDARY. THEY SAID THAT AT 44.64 CHAINS EAST OF THE NORTHWEST CORNER THEY INTERSECTED THE WEST BOUNDARY OF THE SAC & FOX LANDS AT 21.14 CHAINS NORTH OF A STONE SET ON SAID LINE, AND THEY SET A LIMESTONE 19" X 12" X 2" FOR THE CORNER TO FRACTIONAL SECTIONS 19 & 30.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 24, 25 & 30 ON THE WEST TOWNSHIP BOUNDARY
  - 2) 4.64 CHAINS EAST TO THE 19" X 12" X 2-1/2" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX LANDS
  - 3) 36.00 CHAINS EAST TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-13
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SAID THAT **HE SET A STONE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-16-13 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.12 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-16-13 ON THE RANGE LINE, IN THE CENTER OF THE ROAD
  - 2) 4.65 CHAINS EAST TO THE LOCATION FOR THE INDIAN RESERVE LINE ON THE SOUTH LINE OF THE SE1/4 OF SECTION 19-16-13, AT 30 FEET WEST OF A HEDGE
  - 3) 41.43 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-16-13, AT 30 LINKS SOUTH OF A FENCE
  - 4) 81.54 CHAINS EAST TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 29-16-13
  - 5) 121.65 CHAINS EAST TO THE ORIGINAL GOVERNMENT STONE HE FOUND ON THE GROUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 29-16-13
  - 6) 201.67 CHAINS EAST TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 28-16-13
  - 7) 241.78 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 22-16-13

NORTH QUARTER CORNER 30-16-13