

NORTHWEST CORNER SECTION 30, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 96 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 13" X 3"** FOR THE CORNER TO SECTIONS 19 & 30-17-13 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 1, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 10" X 2-1/2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 30-16-13
- 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-16-13
- 3) 40.00 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-16-13
- 4) 44.64 CHAINS EAST TO THE 19" X 12" X 2-1/2" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX LANDS
- 5) 80.64 CHAINS EAST TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-13

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 415 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 574 TO 576 PETITIONED BY C. M. ROBB AND OTHERS FOR TWO ROADS IN TOWNSHIPS 16-12 AND 16-13 [PACKET 1 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 28, 1894, WERE ESTABLISHED AS 50 FOOT WIDE ROADS ON OCTOBER 6, 1894 AS NOTED BY J. A. MILLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED ON JUNE 28, 1895 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 24-16-12 ON THE RANGE LINE ON THE FIRST ROAD AND TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD EXTENDS WEST ON THE SECTION LINES AT 25 FEET EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 24-16-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THE FIRST ROAD CONTINUES EAST ON A STRAIGHT LINE AT 25 FEET EACH SIDE OF THE STRAIGHT LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-16-13 TO END THE FIRST ROAD ON THIS ROAD SURVEY
 - 3) THE SECOND ROAD EXTENDS NORTH ON THE RANGE LINE AT 25 FEET ON EACH SIDE OF THE RANGE LINE TO A ROCK LEDGE AT 876 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 24-16-12, THEN CONTINUES NORTH AS A STRIP OF LAND 50 FEET WIDE ON THE WEST SIDE OF SECTION 19-16-13 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 24-16-12 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE

NECESSARY, SAID THAT **HE FOUND THE STONE IN PLACE IN THE CENTER OF THE ROAD** AT THE SOUTHWEST CORNER OF SECTION 19-16-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.12 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-16-13
 - 2) 44.77 CHAINS EAST TO THE LOCATION FOR THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 19-16-13, AT 30 FEET WEST OF A HEDGE
 - 3) 81.55 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-16-13, AT 30 LINKS SOUTH OF A FENCE
 - 4) 121.66 CHAINS EAST TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 29-16-13
 - 5) 161.77 CHAINS EAST TO THE GOVERNMENT STONE HE FOUND ON THE GROUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SEC. 29-16-13
 - 6) 241.79 CHAINS EAST TO THE **LOCATION** FOR THE NORTHEAST CORNER OF SECTION 28-16-13
 - 7) 281.90 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 22-16-13
- 4) THE KRETSINGER TIE BOOK FOR TOWNSHIP 16-12 SHOWS A **STONE** AT THE "SE CORNER SECTION 24-16-12" ON THE RANGE LINE.
- 1) 28.5' SE TO A REBAR
 - 2) 30.6' NE TO A REBAR
 - 3) 33.7' NW TO A SPIKE & WASHER IN A POST

NORTHWEST CORNER 30-16-13