

NORTHWEST CORNER SECTION 31, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 96 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 3"** FOR THE CORNER TO SECTIONS 30 & 31-16-13 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 1, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 19" X 10" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-16-13
 - 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 12 & 13 EAST AT THE SOUTHWEST CORNER OF SECTION 31-16-13
 - 3) 40.00 CHAINS EAST TO THE 18" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-16-13
 - 4) 44.00 CHAINS EAST TO THE 18" X 10" X 3" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX LANDS
 - 5) 80.10 CHAINS EAST TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 32 & 32-16-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-16-13 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-12; THEN CONTINUES WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN EXTENDS WEST ON THE SECTION LINES FOR 10 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 1-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THIS ROAD SURVEY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION

19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 31-16-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE DETERMINED THE **LOCATION** FOR THE NORTHWEST CORNER OF SECTION 31-16-13 TO BE ON LINE WITH A WIRE FENCE RUNNING SOUTH SAID TO HAVE BEEN SET WHILE THE STONE WAS IN PLACE ON THIS SURVEY. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.99 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 36-16-12
- 2) 43.85 CHAINS EAST TO THE STONE HE FOUND IN PLACE ON THE INDIAN RESERVE LINE ON THE NORTH SIDE OF THE NE1/4 OF SECTION 30-16-13
- 3) 80.05 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 32-16-13
- 4) 100.09 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE NW1/4 OF SECTION 32-16-13
- 5) 120.13 CHAINS EAST TO THE STONE HE SET OF THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-16-13
- 6) 160.21 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-16-13
- 7) 200.24 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-16-13
- 8) 239.28 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-16-13

NORTHWEST CORNER 31-16-13