

**NORTHWEST CORNER SECTION 32, TOWNSHIP 16 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 608 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-16-13.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.05 CHAINS EAST TO THE 20" X 11" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-16-13
  - 2) 80.10 CHAINS EAST TO THE 22" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-16-13
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPT ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 29-16-13 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-12; THEN CONTINUES WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN EXTENDS WEST ON THE SECTION LINES FOR 10 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 3/4 OF A MILE TO THE SOUTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THIS ROAD SURVEY
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHWEST CORNER OF SECTION 19; THE SOUTHWEST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHWEST CORNER, EAST 1/4 CORNER AND THE NORTHWEST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHWEST CORNER, SOUTH 1/4 CORNER AND SOUTHWEST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTHWEST

CORNER OF SECTION 32-16-13 ON THIS **PERMANENT SURVEY** AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-16-13 TO THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 32-16-13 ON THE TOWNSHIP LINE. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 36.20 CHAINS WEST TO THE STONE HE FOUND ON THE INDIAN RESERVE LINE ON THE NORTH SIDE OF THE NE1/4 OF SECTION 31-16-13
- 2) 80.05 CHAINS WEST TO THE LOCATION FOR THE NORTHWEST CORNER OF SECTION 31-16-13 ON THE RANGE LINE, ON LINE WITH A WIRE FENCE TO THE SOUTH SAID TO HAVE BEEN SET WHILE THE STONE WAS IN PLACE
- 3) 120.04 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 36-16-12
- 4) 20.04 CHAINS EAST TO THE STONE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 32-16-13
- 5) 40.08 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-16-13
- 6) 80.16 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-16-13
- 7) 120.19 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 33-16-13
- 8) 159.23 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 33-16-13
- 9) 40.00 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 32
- 10) 80.00 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 32-16-13 ON THE TOWNSHIP LINE
- 11) 80.60 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-16-13 AT 30 LINKS SOUTH OF A FENCE
- 12) 120.64-1/2 CHAINS NORTH TO THE 20" X 8" X 5" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 20-16-13
- 13) 160.69 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 20-16-13

NORTHWEST CORNER 32-16-13