

NORTHEAST CORNER SECTION 34, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 599 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 4"** FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-13 ON THE COUNTY LINE ON OCTOBER 11, 1860.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 SOUTH ON THE COUNTY LINE TO THE 20" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 34 & 35-16-13
 - 2) 80.00 SOUTH ON THE COUNTY LINE TO THE 22" X 16" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 34 & 35-16-13 ON THE TOWNSHIP LINE
 - 3) 40.00 CHAINS WEST TO THE 36" X 24" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-16-13
 - 4) 80.00 CHAINS WEST TO THE 24" X 15" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-13
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 129 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 102 TO 104 PETITIONED BY M. LUNGREN AND OTHERS FOR A ROAD IN TOWNSHIP 16-13 ON THE LYON AND OSAGE COUNTY LINE [PACKET 381 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 24, 1881, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 5 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-16-13 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE COUNTY LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-16-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 233 DATED SEPTEMBER 24, 1881, FOR A ROAD SURVEY IN TOWNSHIP 16-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 5 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-16-13 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE COUNTY LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-16-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY.
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 ON THE LYON AND OSAGE COUNTY LINE TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 28-16-13 ACCORDING TO HIS SURVEY NOTES AND DRAWING
 - 2) THIS ROAD CONTINUES AT THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12 AND CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 AND 579 FOR ROAD NUMBER 248 BY A PETITION BY L. W. HUTCHINSON [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JANUARY 1884, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 AT THE EAST LINE OF LYON COUNTY TO END THIS ROAD SURVEY.
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 9 DATED FEBRUARY 27 & 28, 1884 FOR A COUNTY ROAD IN TOWNSHIP 16, RANGES 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 ON THE LYON AND OSAGE COUNTY LINE TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES WITH ANGLE POINTS IN THE SE1/4 OF SECTION 29-16-13 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-16-12; THEN TURNS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-16-12 TO BEGIN THIS ROAD SURVEY.
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 48, AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 48 DATED AUGUST 4, 1884 PER THE AGREEMENT OF T. GALUTIA, A. G. GALUTIA, A. R. GALUTIA, GEORGE W. KIBBE, Y. ALBION DAVIDSON AND ANDREW DAVIDSON TO SUBDIVIDE SECTION 27-16-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS AGREEMENT SURVEY. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 27-16-13 TO SET A STONE FOR THE SOUTHWEST CORNER OF SECTION 27-16-13 ON THIS AGREEMENT SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,653' NORTH ON THE COUNTY LINE TO THE STONE HE SET FOR AN AGREEMENT CORNER
 - 2) 2,645' NORTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-16-13
 - 3) 3,306' NORTH ON THE COUNTY LINE TO THE STONE HE SET FOR AN AGREEMENT CORNER
 - 4) 5,288' NORTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-16-13
- 8) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 134, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 105 DATED FEBRUARY 16 & 17, 1888 FOR A ROAD IN TOWNSHIP 16, RANGE 13, SAID THAT **HE FOUND AND MARKED THE EXISTING STONE IN ITS ORIGINAL POSITION** AT THE NORTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE ORIGINAL STONE

HE FOUND AND MARKED AT THE SOUTHWEST CORNER OF SECTION 27-16-13; THEN EXTENDS NORTH ON THE SECTION LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE SANDSTONE HE FOUND IN ITS NATURAL BED AND HE MARKED FOR THE NORTHWEST CORNER OF SECTION 27-16-13, THEN EXTENDS WEST ON THE SECTION LINES AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/4 MILE TO THE ROAD STONE MARKED "R" HE SET TO END THIS ROAD SURVEY

- 2) **NOTE:** THE LAST 1-1/4 MILE WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS
- 9) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 262 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 398 TO 400 PETITION BY C. OTTO JOHNSON FOR A ROAD IN TOWNSHIP 16-13 COMMENCING ON THE SECTION LINE RUNNING EAST AND WEST BETWEEN SECTIONS 27 AND 34 I TOWNSHIP 16, RANGE 13 AT THE PLACE WHERE SAID SECTION LINE INTERSECTS THE BOUNDARY BETWEEN LYON AND OSAGE COUNTIES, THENCE WEST ONE MILE ON SAID SECTION LINE, THENCE NORTH ONE MILE ON THE SECTION LINE, THENCE WEST ABOUT 1-1/4 MILES ON THE SECTION LINE TO A POINT WHERE THE SECTION LINE INTERSECTS THE ROAD RUNNING NORTH AND SOUTH [PACKET 611 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 16, 1888, SAID THAT **HE FOUND AND MARKED THE EXITING STONE IN ITS ORIGINAL POSITION** AT THE NORTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE TO BEGIN THIS ROAD SURVEY. ON OCTOBER 4, 1888 THE BOARD OF COUNTY COMMISSIONERS ESTABLISHED AT 60 FEET WIDE FOR THE EAST AND WEST ROAD, AND 50 FEET WIDE FOR THE NORTH AND SOUTH ROAD, FROM THE SOUTHEAST CORNER OF SECTION 27-16-13, THENCE WEST ONE MILE, THENCE NORTH ONE MILE TO THE NORTHWEST CORNER OF SECTION 27-16-13 ONLY, THE THIRD MILE WAS **REJECTED** AS NOTED BY J. S. GRIMSLEY, CHAIRMAN, AND RECORDED BY ROLAND LAKIN, COUNTY CLERK, ON JANUARY 30, 1889. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE ORIGINAL STONE HE FOUND AND MARKED AT THE SOUTHWEST CORNER OF SECTION 27-16-13; THEN EXTENDS NORTH ON THE SECTION LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE SANDSTONE HE FOUND IN ITS NATURAL BED AND HE MARKED FOR THE NORTHWEST CORNER OF SECTION 27-16-13, THEN EXTENDS WEST ON THE SECTION LINES AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/4 MILE TO THE ROAD STONE MARKED "R" HE SET TO END THIS ROAD SURVEY
 - 2) **NOTE:** THE LAST 1-1/4 MILE WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS
- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 173 AND DATED MAY 1904, ORDERED BY J. W. MAVITY, OSAGE COUNTY SURVEYOR AT THE REQUEST OF J. J. DAHL, AGENT FOR TILLIE SLUSSER, AND CHARLES LINDBLOOM OF OSAGE COUNTY FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE EAST LINE OF SECTION 3-17-13 AND THE EAST LINE OF SECTION 34-16-13 ON THE OSAGE COUNTY LINE AND RUN SUCH LINES AS NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS JOINT **PERMANENT SURVEY** WITH OSAGE COUNTY. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 46 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN

PACKET "M 135" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.42 CHAINS SOUTH ON THE COUNTY LINE TO THE GOVERNMENT STONE HE FOUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 34-16-13 [**NOTE:** HE MOVED THE TEMPORARY STAKE 8 LINKS SOUTH OF THE 40 CHAIN MARK, MAKING THIS DISTANCE **39.92 CHAINS** TO BE ONE-HALF OF THE TOTAL DISTANCE OF 79.84 CHAINS – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 79.84 CHAINS SOUTH ON THE COUNTY LINE TO THE 22" X 9" X 2" STONE WITH A "+" ON THE SOUTH SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 3-17-13
 - 3) 119.34 CHAINS SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 3-17-13
 - 4) 159.16 CHAINS SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-17-13 AT THE CORNER TO A STONE WALL
- 11) COMMISSIONERS ROAD JOURNAL BOOK "B" ON PAGE 110:
IT WAS NOTED THAT THE FOLLOWING ROAD WAS **CLOSED** UNDER THE PROVISIONS OF 68-102 OF THE GENERAL STATUTES 1953 SUPPLEMENT BY A RESOLUTION OF THE BOARD OF COUNTY COMMISSIONERS DATED JANUARY 28, 1958:
- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 34-16-13 RUNNING THENCE EAST 1 MILE AND THERE ENDING.

NORTHEAST CORNER 34-16-13