

NORTHWEST CORNER SECTION 34, TOWNSHIP 16 SOUTH, RANGE 13 EAST

- 1) ON PAGE 601 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 15" X 3"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST TO THE 36" X 24" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-16-13
 - 2) 80.00 CHAINS EAST TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-13 ON THE COUNTY LINE

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-13 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE *SE*1/4 OF SECTION 28-16-13 ACCORDING TO HIS SURVEY NOTES AND DRAWING
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE TO THE STONE HE FOUND ON THE EAST LINE OF LYON COUNTY AT THE SOUTHEAST CORNER OF SECTION 27-16-13 TO END THIS ROAD SURVEY
 - 3) THIS ROAD CONTINUES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12 AND CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 48, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 48 DATED AUGUST 4, 1884 PER THE AGREEMENT OF T. GALUTIA, A. G. GALUTIA, A. R. GALUTIA, GEORGE W. KIBBE, Y. ALBION DAVIDSON AND ANDREW DAVIDSON TO SUBDIVIDE SECTION 27-16-13, SAID THAT **HE SET A STONE** FOR THE SOUTHWEST CORNER OF SECTION 27-16-13 AT THE INTERSECTION OF THE LINE FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-13 THROUGH THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF 27-16-13 WITH THE LINE FROM THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-13 THROUGH THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 27-16-13 ON THIS **AGREEMENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,322' NORTH TO THE STONE HE SET FOR THE WEST 1/4 OF 1/4 CORNER OF THE SW1/4 OF SECTION 27-16-13
 - 2) 2,644' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-16-13

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 134, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 105 DATED FEBRUARY 16 & 17, 1888 FOR A ROAD IN TOWNSHIP 16, RANGE 13, SAID THAT **HE FOUND AND MARKED THE EXISTING STONE** AT THE NORTHEAST CORNER OF SECTION 33-16-13 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE ORIGINAL STONE HE FOUND AND MARKED AT THE NORTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE SANDSTONE HE FOUND IN ITS NATURAL BED AND HE MARKED FOR THE NORTHWEST CORNER OF SECTION 27-16-13, THEN EXTENDS WEST ON THE SECTION LINES AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/4 MILE TO THE ROAD STONE MARKED "R" HE SET TO END THIS ROAD SURVEY
 - 3) **NOTE:** THE LAST 1-1/4 MILE WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 262 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 398 TO 400 PETITION BY C. OTTO JOHNSON FOR A ROAD IN TOWNSHIP 16-13 COMMENCING ON THE SECTION LINE RUNNING EAST AND WEST BETWEEN SECTIONS 27 AND 34 I TOWNSHIP 16, RANGE 13 AT THE PLACE WHERE SAID SECTION LINE INTERSECTS THE BOUNDARY BETWEEN LYON AND OSAGE COUNTIES, THENCE WEST ONE MILE ON SAID SECTION LINE, THENCE NORTH ONE MILE ON THE SECTION LINE, THENCE WEST ABOUT 1-1/4 MILES ON THE SECTION LINE TO A POINT WHERE THE SECTION LINE INTERSECTS THE ROAD RUNNING NORTH AND SOUTH [PACKET 611 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 16, 1888, SAID THAT **HE FOUND AND MARKED THE EXITING STONE IN ITS ORIGINAL POSITION** AT THE NORTHWEST CORNER OF SECTION 34-16-13 ON THIS ROAD SURVEY. ON OCTOBER 4, 1888 THE BOARD OF COUNTY COMMISSIONERS ESTABLISHED AT 60 FEET WIDE FOR THE EAST AND WEST ROAD, AND 50 FEET WIDE FOR THE NORTH AND SOUTH ROAD, FROM THE SOUTHEAST CORNER OF SECTION 27-16-13, THENCE WEST ONE MILE, THENCE NORTH ONE MILE TO THE NORTHWEST CORNER OF SECTION 27-16-13 ONLY, THE THIRD MILE WAS **REJECTED** AS NOTED BY J. S. GRIMSLEY, CHAIRMAN, AND RECORDED BY ROLAND LAKIN, COUNTY CLERK, ON JANUARY 30, 1889. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 4) THIS ROAD EXTENDS EAST ON THE SECTION LINE AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE ORIGINAL STONE HE FOUND AND MARKED AT THE NORTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 5) THIS ROAD EXTENDS NORTH ON THE SECTION LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR ONE MILE TO THE SANDSTONE HE FOUND IN ITS NATURAL BED AND HE MARKED FOR THE NORTHWEST CORNER OF SECTION 27-16-13, THEN EXTENDS WEST ON THE SECTION LINES AT 60 FEET WIDE, 30 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/4 MILE TO THE ROAD STONE MARKED "R" HE SET TO END THIS ROAD SURVEY
 - 6) **NOTE:** THE LAST 1-1/4 MILE WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 173 AND DATED MAY 1904, ORDERED BY J. W. MAVITY, OSAGE COUNTY SURVEYOR AT THE REQUEST OF J. J. DAHL, AGENT FOR TILLIE SLUSSER, AND CHARLES LINDBLOOM OF OSAGE COUNTY FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE EAST LINE OF SECTION 3-17-13, AND THE EAST LINE OF SECTION 34-16-13 ON THE OSAGE COUNTY LINE, AND RUN SUCH LINES AS NECESSARY TO PROPERLY COMPLETE THE WORK, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-16-13 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 46 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 135" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

CONTINUED ON PAGE 3

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHEAST CORNER OF SECTION 33-16-13 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.04 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 33-16-13
 - 2) 79.07 CHAINS WEST TO THE STAKE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-16-13
 - 3) 119.15 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-16-13
 - 4) 139.19 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 32-16-13
 - 5) 159.23 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 32-16-13
 - 6) 195.43 CHAINS WEST TO THE STONE HE FOUND IN PLACE ON THE INDIAN RESERVE LINE ON THE NORTH SIDE OF THE NE1/4 OF SECTION 31-16-13
 - 7) 239.28 CHAINS WEST TO THE LOCATION FOR THE NORTHWEST CORNER OF SECTION 31-16-13 ON THE RANGE LINE, ON LINE WITH A FENCE RUNNING SOUTH SAID TO HAVE BEEN SET WHILE THE STONE WAS IN PLACE
 - 8) 279.27 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 36-16-12
- 8) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 121
ON MARCH 17, 1930 A PETITION SIGNED BY A. G. PETERSON AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 16-13 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JUNE 20, 1930, AND THE FINAL ORDER WAS ISSUED ON AUGUST 9, 1930 THAT THE ROAD WILL BE LOCATED IN PART AS FOLLOWS:
- 1) BEGINNING AT THE SOUTHEAST CORNER OF SECTION 28-16-13; THENCE RUNNING WEST THREE QUARTERS OF A MILE ON THE SECTION LINE BETWEEN SECTIONS 28 & 33-16-13 AND ENDING THERE
 - 2) SAID ROAD TO BE OPENED 40 (FORTY) FEET WIDE, BEING 20 (TWENTY) FEET ON EACH SIDE OF THE SECTION LINE
 - 3) THIS REPORT FURTHER PROVIDES FOR A FIFTY FOOT RADIUS CURVE OFF OF THE SOUTHEAST CORNER OF THE SOUTHEAST QUARTER OF SAID SECTION 28 TO CONNECT THIS ROAD WITH THE NORTH AND SOUTH ROAD ALONG THE EAST SIDE OF SECTION 28
 - 4) THE REMAINING PORTION OF THE PETITION IS **NOT ALLOWED**
- 9) O. D. HENRY, COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 739 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 98 PETITIONED BY A. G. PETERSON AND OTHERS FOR A ROAD IN TOWNSHIP 16-13 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON AUGUST 9, 1930

SHOWS ON HIS SURVEY DRAWING THAT HE APPARENTLY **FOUND** THE SOUTHEAST CORNER OF SECTION 28-16-13 TO BEGIN THIS ROAD SURVEY. THE VIEWERS RECOMMENDED THAT THE FOLLOWING ROAD SHOULD BE OPENED:

- 1) BEGINNING AT THE SOUTHEAST CORNER OF SECTION 28-16-13; THENCE RUNNING WEST FOR 3/4 OF A MILE ON THE SECTION LINE BETWEEN SECTIONS 28 AND 33-16-13 AND ENDING THERE
 - 2) SAID ROAD TO BE OPENED 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE SECTION LINE
 - 3) THIS REPORT FURTHER PROVIDES FOR A 50 FOOT RADIUS CURVE OFF OF THE SOUTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-12 TO CONNECT THIS ROAD WITH THE NORTH AND SOUTH ROAD ALONG THE EAST SIDE OF SECTION 28-16-13
 - 4) THE REMAINDER PORTION OF THIS PETITION IS **NOT** ALLOWED
- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-13 SHOWS A **STONE AND PIN** AT THE "SE CORNER SECTION 28-16-13".
- 1) 28.5' NE TO A NAIL IN A FENCE POST
 - 2) 18.5' EAST TO A NAIL IN A FENCE POST
 - 3) 26.7' SE TO A NAIL IN A FENCE POST
- 11) COMMISSIONERS ROAD JOURNAL BOOK "B" ON PAGE 110:
IT WAS NOTED THAT THE FOLLOWING ROAD WAS **CLOSED** UNDER THE PROVISIONS OF 68-102 OF THE GENERAL STATUTES 1953 SUPPLEMENT BY A RESOLUTION OF THE BOARD OF COUNTY COMMISSIONERS DATED JANUARY 28, 1958:
- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 34-16-13 RUNNING THENCE EAST 1 MILE AND THERE ENDING.

NORTHWEST CORNER 34-16-13