

NORTH 1/4 CORNER SECTION 01, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 56 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 1-17-10 ON THE TOWNSHIP LINE ON JANUARY 9, 1861.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-17-10
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 20" X 10" X 8" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST AT THE NORTHEAST CORNER OF SECTION 1-17-10

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 171, A **CONSENT SURVEY** OF ALL INTERESTED PARTIES RECORDED IN SURVEY BOOK "E" ON PAGE 171 DATED JUNE 9, 1887 TO LOCATED THE CENTER AND EAST 1/4 CORNERS OF SECTION 1-17-10, SAID THAT THE STONE WAS **OUT** AT THE NORTH 1/4 CORNER OF SECTION 1-17-10 ON THE TOWNSHIP LINE. HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-17-10 EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-17-10 ON THE RANGE LINE, AND HE DROVE A **TEMPORARY STAKE** FOR THE NORTH 1/4 CORNER OF SECTION 1-17-10 AT THE PROPORTIONAL DISTANCE BETWEEN THESE TWO FOUND STONES ON THE TOWNSHIP LINE ON THIS **CONSENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645-2/3' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-17-10 ON THE RANGE LINE
- 2) 2,645-2/3' WEST ON THE TOWNSHIP LINE TO THE **THEORETICAL LOCATION** FOR THE NORTHWEST CORNER OF SECTION 1-17-10
- 3) 5,291-1/3' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-17-10

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 2, 2006 FOR PROJECT NUMBER 06292-02 TO SURVEY THE NORTH LINE OF SECTION 1-17-10 AND THE SOUTH LINE OF SECTION 36-16-10 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 06-KT, SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, SAID THAT HE DEEMED THAT THE NORTH 1/4 CORNER OF SECTION 1-17-10 ON THE TOWNSHIP LINE WAS **LOST** AS IT HAD NOT BEEN FOUND ON PREVIOUS PERMANENT SURVEYS. **HE SET A 5/8" X 24" REBAR WITH LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 1-17-10 ON TRUE TOWNSHIP LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER OF SECTION 1-17-10 AND THE NORTHEAST CORNER OF SECTION 1-17-10.

- 1) 32.75' SW TO A SPIKE & WASHER IN THE TOP OF A BRACE POST
- 2) 27.05' SOUTH TO A SPIKE & WASHER IN A CORNER FENCE POST
- 3) 26.55' NW TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) 30.10' NORTH TO A LINE OF FENCE TO THE WEST
- 5) 27.0' SOUTH TO A LINE OF FENCE TO THE EAST
- 6) IN LINE WITH A FENCE TO THE SOUTH
- 7) 2.0' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,650.31' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 1-17-10
- 2) 1,250.31' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
- 3) 2,050.31' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
- 4) 2,650.31' EAST ON THE TOWNSHIP LINE TO THE 5" X 8" LIMESTONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 1-17-10 ON THE RANGE LINE, AT THE PLACE INDICATED BY OLD TIES HE FOUND AT THE OFFICE OF THE COUNTY ENGINEER

NORTH QUARTER CORNER 01-17-10