

WEST 1/4 CORNER SECTION 03, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 155 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.25 CHAINS NORTH TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 33 & 34 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 23 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 78 DATED MAY 12, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 4-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,321-1/2' WEST TO THE 24" X 12" X 4" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 4-17-10
 - 2) 2,643' WEST TO THE 18" X 10" X 5" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 4-17-10
 - 3) 3,967' WEST TO THE 24" X 12" X 2" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-17-10
 - 4) 5,291' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 4-17-10

- 3) IN THE SURVEY FOLDER FOR TOWNSHIP 17-10, ON A SURVEY LABELED "SURVEY FOR SCOTT MOUSE HOCH" WITH NO NAME OR DATE SHOWS A **STONE** AT THE WEST 1/4 CORNER OF SECTION 3-17-10.
 - 1) 33' NW TO A STONE GATE POST
 - 2) 33.2' SW TO A STONE GATE POST
 - 3) 27.5' NE TO A STONE GATE POST

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **STONE** AT THE "SW CORNER NW1/4 SECTION 3-17-10" AND "E1/4 CORNER SECTION 04-17-10".
 - 1) 33' NW TO A STONE GATE POST
 - 2) 33.2' SW TO A STONE GATE POST
 - 3) 30.0' NE TO A STONE CORNER POST

- 5) KRETSINGER TIE BOOK NUMBER 13 ON PAGE 34 AT THE TOP OF THE PAGE SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 3-17-10" ON MARCH 22, 1934.
 - 1) 33' NW TO A STONE GATE POST
 - 2) 33.2' SW TO A STONE GATE POST
 - 3) 27.5' NE TO A STONE GATE POST

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 02, 2002, FOR PROJECT NUMBER 02263-02 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT BRIDGE REPLACEMENT PROJECT NUMBER 02-AG, SAID THAT HE DUG WITH A COUNTY MAINTAINER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 3-17-10. **HE FOUND A 4" X 10" LIMESTONE THAT WAS LEANING TO THE WEST** AT THE WEST 1/4 CORNER OF SECTION 3-17-10.

HIS TIES ARE ON PAGE 2

- 1) 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET FLUSH WITH THE TOP OF THE STONE AND OVER THE CENTER OF THE STONE
- 2) 1/2" REBAR WITH HIS CAP SET ON THE WEST SIDE OF THE STONE
- 3) IN LINE WITH FENCES TO THE EAST AND WEST
- 4) 33.3' SE TO A 40 D SPIKE & WASHER IN A POWER POLE
- 5) 33.5' WSW TO A CONCRETE NAIL & BOTTLE CAP IN A FENCE GATE POST
- 6) 27.35' WNW TO A CONCRETE NAIL & BOTTLE CAP IN A BRACE POST
- 7) 26.3' EAST TO A LINE OF FENCE TO THE SOUTH
- 8) 26.3' WEST TO A LINE OF FENCE TO THE NORTH

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 1,883.30' SOUTH TO THE 1/2" REBAR WITH A "GEOTECH" CAP HE SET ON THE SECTION LINE FOR A P.O.T.
- 2) 2,413.30' SOUTH TO THE 1/2" REBAR WITH A "GEOTECH" CAP HE SET ON THE SECTION LINE FOR A P.O.T.
- 3) 2,663.30' SOUTH TO THE 3" X 3" LIMESTONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-17-10

WEST QUARTER CORNER 03-17-10