

NORTH 1/4 CORNER SECTION 04, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 55 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 4-17-10 ON THE TOWNSHIP LINE ON JANUARY 9, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-17-10
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-17-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 23 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 78 DATED MAY 12, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 4-17-10 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

- 3) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' NORTH TO A WITNESS PIN
 - 2) SEE BOOKS 30 & 31

NORTH QUARTER CORNER SECTION 04-17-10