

WEST 1/4 CORNER SECTION 04, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 159 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 13" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-17-10 ON MARCH 2, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 41.00 CHAINS NORTH TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 32 & 33 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 23 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 78 DATED MAY 12, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,320' SOUTH TO THE POST HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-17-10
 - 2) 2,640' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-17-10
 - 3) 1,324' EAST TO THE 24" X 12" X 2" LIMESTONE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-17-10
 - 4) 2,648' EAST TO THE 18" X 10" X 5" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 4-17-10
 - 5) 3,969-1/2' EAST TO THE 24" X 12" X 4" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 4-17-10
 - 6) 5,291' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 4-17-10

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 39 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 158 & 159 PETITION BY SAMUEL SOWERS AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 136 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1879, WERE ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 5-17-10 ON THE FIRST ROAD ON THIS ROAD SURVEY.
[NOTE: SEE THE RECORD FOR THE EXISTING ROAD FROM THE SOUTHEAST CORNER OF SECTION 32-16-10 THAT EXTENDED SOUTHEASTERLY AND THEN SOUTHWESTERLY TO THE SOUTHWEST CORNER OF LOT 4 IN THE SOUTHEAST CORNER OF SECTION 5-17-10 WAS VACATED ON THIS ROAD SURVEY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS FIRST ROAD EXTENDS NORTH ON THE SECTION LINES TO A POINT 391' NORTH OF THE EAST 1/4 CORNER OF SECTION 20-16-10 TO AN ANGLE TO THE NORTHEASTERLY; THEN INTERSECTS THE SECTION LINE AT 1,653' SOUTH OF THE SOUTHEAST CORNER OF SECTION 17-16-10; THEN CONTINUES NORTH ON THE SECTION LINES FOR 1,653' TO THE NORTHEAST CORNER OF SECTION 17-16-10 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THIS FIRST ROAD EXTENDS EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 4-17-10 AT A TURN TO THE SOUTH ON THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 141 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 150 TO 152 \ PETITIONED BY P. E. SOWERS AND OTHERS FOR A COUNTY ROAD IN SECTION 4-17-10 [PACKET 387 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1881 AND THE TRUSTEE WAS NOTIFIED TO OPEN AS A 40 FOOT WIDE ROAD, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 4-17-10 ON THIS ROAD SURVEY.
HI SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 2,640 FEET TO THE NORTHWEST CORNER OF SECTION 4-17-10 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 1,320 FEET TO THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 4-17-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 230 DATED SEPTEMBER 5, 1881, FOR A ROAD SURVEY IN TOWNSHIP 17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 4-17-10 AT AN ANGLE POINT ON THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH FOR 2,640' ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-17-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST FOR 1,320' ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 4-17-10 AT TERMINUS OF THIS ROAD SURVEY
- 6) IN THE SURVEY FOLDER FOR TOWNSHIP 17-10 IN A SURVEY LABELED "SURVEY FOR SCOTT MOUSE HOCH" WITH NO NAME OR DATE IT SHOWS A **STONE** AT THE WEST 1/4 CORNER OF SECTION 4-17-10.
- 1) 17.7' TO T C S
- 7) IN THE KRETSINGER TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 04-17-10" ON JANUARY 16, 1964.
- 1) 25.2' SW TO A SPIKE IN THE TOP OF A FENCE POST
 - 2) 25.4' NW TO A SPIKE IN THE TOP OF A FENCE POST

WEST QUARTER CORNER 04-17-10