

NORTH 1/4 CORNER SECTION 05, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 55 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 5-17-10 ON THE TOWNSHIP LINE ON JANUARY 9, 1861.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 28" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-18-13
 - 2) 7.85 CHAINS EAST ON THE TOWNSHIP LINE TO THE EAST BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVATION AT THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE FRACTIONAL CORNER TO SECTIONS 5 & 32
 - 3) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-17-10
- 2) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 3, 1991, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, A CORRECTED SURVEY FOR THE WALKUP & DENISON SURVEY TO LOCATE AND STAKE THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 32-16-10 RECORDED IN VOLUME 459 ON PAGE 558 IN THE REGISTER OF DEEDS OFFICE ON JUNE 5, 1991, SAID THAT HE HAD A COUNTY BLADEMAN EXCAVATE FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 32-16-10 ON THE TOWNSHIP LINE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 32-16-10 ON THE TOWNSHIP LINE IN THE CENTER OF THE ROAD RIGHT-OF-WAY AND EQUIDISTANT BETWEEN THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 32-16-10.

- 1) 27.0' SE TO A NAIL IN THE TOP OF A POST
- 2) 25.3' SSW TO A NAIL IN TOP OF A POST
- 3) 37.3' SW TO A NAIL IN THE TOP OF A POST

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 2,620.80' WEST ON THE TOWNSHIP LINE TO THE 1/2" PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 32-16-10
- 2) 2,628.80' EAST ON THE TOWNSHIP LINE TO THE PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-16-10
- 3) 2,663.57' NORTH TO THE **COMPUTED** LOCATION FOR THE CENTER CORNER OF SECTION 32-16-10
- 4) 3,993.67' NORTH TO THE 1/2" PIN HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 32-16-10
- 5) 5,323.77' NORTH TO THE PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-16-10

NORTH QUARTER CORNER 05-17-10