

WEST 1/4 CORNER SECTION 08, TOWNSHIP 17 SOUTH, RANGE 10 EAST

1) ON PAGE 165 OF THE GLO ORIGINAL FILED NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-17-10.

2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 93, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 99 DATED JUNE 17-30, 1886 AND RECORDED IN MISCELLANEOUS VOLUME 36 ON PAGES 495 & 496 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886, TO ESTABLISH THE MISSING CORNERS AND SUBDIVIDE SECTION 7-17-10, SAID THAT **HE SET A 22" X 18" X 6" STONE MARKED "1/4" ON THE WEST FACE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 7-17-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-17-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.83-1/2 CHAINS NORTH TO THE 20" X 9" X 6" STONE MARKED "1/8" ON THE WEST FACE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 7-17-10
- 2) 39.87 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-17-10
- 3) 39.87 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-10
- 4) 20.00 CHAINS WEST TO THE 16" X 9" X 3" STONE MARKED "1/8" ON THE NORTH FACE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 7-17-10
- 5) 40.00 CHAINS WEST TO THE 19" X 12" X 2-1/2" STONE MARKED "+" ON THE TOP AND NEAR THE BOTTOM HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 7-17-10

3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2010 FOR PROJECT NUMBER 10053-02, A SURVEY OF THE SOUTHEAST 1/4 OF SECTION 8-17-10 FOR DON DIX, SURVEY F08003 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE EXCAVATED FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 8-17-10 WITH A COUNTY MAINTAINER. **HE FOUND THE 12" X 6" LIMESTONE THAT WAS SET BY EDMISTON IN 1886** IN SURVEY BOOK "F" ON PAGE 99 AT THE WEST 1/4 CORNER OF SECTION 8-17-10. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP ON THE EAST SIDE CENTER OF THE STONE AND A 5/8" X 30" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE CENTER OF THE STONE.**

- 1) 19.65' EAST TO A CONCRETE NAIL & BOTTLECAP IN THE SIDE OF A FIBER OPTIC SIGN POST
- 2) 32.00' SW TO A CONCRETE NAIL & BOTTLECAP IN THE SIDE OF A FIBER OPTIC SIGN POST
- 3) 24.65' WEST TO THE SOUTHEAST CORNER OF A STONE CORNER FENCE POST
- 4) 40.05' NW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH GATE POST
- 5) IN LINE OF FENCE TO THE WEST EXTENDED
- 6) IN THE CENTERLINE TRAVELED WAY OF ROAD "B" NORTH AND SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,651.18' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 8-17-10
- 2) 2,655.45' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 8-17-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,633.85' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 8-17-10
- 4) 5,264.05' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 8-17-10

WEST QUARTER CORNER 08-17-10