

NORTH 1/4 CORNER SECTION 09, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 159 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.01 CHAINS WEST TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9
 - 2) 40.02 CHAINS EAST TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 23 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 78 DATED MAY 12, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,325' NORTH TO THE 16" X 10" X 3" LIMESTONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-17-10
 - 2) 2,650' NORTH TO THE 18" X 10" X 5" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 4-17-10
 - 3) 1,324' EAST TO THE 18" X 6" X 4" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 4-17-10
 - 4) 2,648' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 4-17-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 59, A **PERMANENT SURVEY** FOR THE PURPOSE OF LOCATING THE CORNERS, BOUNDARIES, AND SUBDIVISIONS OF SECTION 9-17-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK AT THE REQUEST OF CHARLES WILKINSON RECORDED IN SURVEY BOOK "F" ON PAGE 138 DATED NOVEMBER 12, 1902, SAID THAT **HE FOUND THE GOVERNMENT 1/4 STONE** AT THE NORTH 1/4 CORNER OF SECTION 9-17-10 ON THIS **PERMANENT SURVEY**. SEE ALSO PACKED "M 133" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS LEGAL SURVEY. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 98 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.10-1/2 CHAINS WEST TO THE 18" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 9-17-10
 - 2) 40.21 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-17-10
 - 3) 20.12 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 9-17-10 THAT WAS SET BY MILLIKEN
 - 4) 40.21 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-10
 - 5) 20.08 CHAINS SOUTH TO THE 18" X 6" X 2" STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER O OF THE NE1/4 OF SECTION 9-17-10
 - 6) 40.16 CHAINS SOUTH TO THE 20" X 12" X 2" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 9-17-10

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 26, 2002, FOR PROJECT NUMBER 02264-02, SAID THAT **HE FOUND THE REMAINS OF THE FRACTURED GLO STONE AT 6" BELOW**

THE ROAD SURFACE AT THE NORTH 1/4 CORNER OF SECTION 9-17-10 FROM A RETRACEMENT OF A PERMANENT SURVEY BY ALVA J. SMITH IN 1902 AND RECORDED IN SURVEY BOOK "F" ON PAGE 138.

- 1) A 5/8" X 24" REBAR WITH A LYON COUNTY CAP WAS SET AT THE CENTER OF THE STONE AND 3" BELOW THE SURFACE
- 2) A 5/8" X 24" REBAR WITH A LYON COUNTY CAP WAS SET AT 4" BELOW THE SOUTH SIDE OF THE STONE
- 3) 34.6' NW TO A PK NAIL & SHINER SET IN A HEDGE FENCE POST
- 4) 20.3' SSE TO A PK NAIL & SHINER SET IN A CORNER FENCE POST
- 5) 30.2' NE TO A PK NAIL & SHINER SET IN A HEDGE FENCE POST
- 6) 20.0' SOUTH TO A LINE OF FENCE EAST-WEST
- 7) 26.5' NORTH TO A LINE OF FENCE EAST-WEST
- 8) 4.0' EAST TO A LINE OF FENCE TO THE SOUTH

NORTH QUARTER CORNER 09-17-10