

NORTH 1/16 CORNER OF THE NORTHWEST 1/4 SECTION 09, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 39 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 158 & 159 PETITION BY SAMUEL SOWERS AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 136 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1879, WERE ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10 ON THE FIRST AND SECOND ROAD ON THIS ROAD SURVEY. **[NOTE:** SEE THE RECORD FOR THE EXISTING ROAD FROM THE SOUTHEAST CORNER OF SECTION 32-16-10 THAT EXTENDED SOUTHEASTERLY AND THEN SOUTHWESTERLY TO THE SOUTHWEST CORNER OF LOT 4 IN THE SOUTHEAST CORNER OF SECTION 5-17-10 THAT WAS VACATED ON THIS ROAD SURVEY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS FIRST ROAD EXTENDS NORTH TO THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 4-17-10 AT A TURN TO THE WEST
 - 2) THIS FIRST ROAD EXTENDS EAST ON THE SECTION LINE FOR 3,960 FEET TO THE SOUTHEAST CORNER OF SECTION 4-17-10 AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
 - 3) THE SECOND ROAD COMMENCES AT THIS CORNER AND EXTENDS WEST TO THE SOUTHWEST CORNER OF SECTION 4-17-10 AT A TURN TO THE SOUTH ON THIS ROAD SURVEY
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 59, A **PERMANENT SURVEY** FOR THE PURPOSE OF LOCATING THE CORNERS, BOUNDARIES, AND SUBDIVISIONS OF SECTION 9-17-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK AT THE REQUEST OF CHARLES WILKINSON RECORDED IN SURVEY BOOK "F" ON PAGE 138 DATED NOVEMBER 12, 1902, SAID THAT **HE SET AN 18" X 12" X 3" STONE** FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 9-17-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-17-10 AND THE GOVERNMENT STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-17-10 ON THIS **PERMANENT SURVEY**. SEE ALSO PACKED "M 133" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS LEGAL SURVEY. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 98 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 20.10-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-17-10
 - 2) 20.10-1/2 CHAINS EAST TO THE GOVERNMENT STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-17-10
 - 3) 40.22-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NORTHEAST CORNER OF SECTION 9-17-10 THAT WAS SET BY MILLIKEN
 - 4) 60.31-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-10
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 26, 2002, FOR PROJECT NUMBER 02264-02, SAID THAT **HE FOUND A 10" X 5" STONE** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 9-17-10 FROM A PERMANENT SURVEY BY ALVA J. SMITH IN 1902 AND RECORDED IN SURVEY BOOK "F" ON PAGE 138. **HE SET A 1/2"**

X 12" REBAR WITH HIS "LS 752" CAP ON THE SOUTH SIDE AND AT THE CENTER OF THE STONE.

- 1) 41.1' NW TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
- 2) 37.05' NE TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
- 3) 25.6' SE TO A CONCRETE NAIL & SHINER IN A FENCE BRACE POST
- 4) 6.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 09-17-10