

NORTHWEST CORNER SECTION 09, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 158 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.01 CHAINS EAST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-18-10
 - 2) 80.03 CHAINS EAST TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-18-10
 - 3) 31.50 CHAINS WEST TO THE 18" X 14" X 4" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVE
 - 4) 40.00 CHAINS WEST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-17-10
 - 5) 80.00 CHAINS WEST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-17-10
 - 6) 40.00 CHAINS NORTH TO THE 22" X 13" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-18-10
 - 7) 81.00 CHAINS NORTH TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 32 & 33 ON THE TOWNSHIP LINE

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 23 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 78 DATED MAY 12, 1874 TO ESTABLISH THE CENTER CORNER AND THE CORNERS OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 4-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,320' NORTH TO THE POST HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-17-10
 - 2) 2,640' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 4-17-10

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 39 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 158 & 159 PETITION BY SAMUEL SOWERS AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 136 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1879, WERE ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 4-17-10 ON THE SECOND ROAD ON THIS ROAD SURVEY. **[NOTE: SEE THE RECORD FOR THE EXISTING ROAD FROM THE SOUTHEAST CORNER OF SECTION 32-16-10 THAT EXTENDED SOUTHEASTERLY AND THEN SOUTHWESTERLY TO THE SOUTHWEST CORNER OF LOT 4 IN THE SOUTHEAST CORNER OF SECTION 5-17-10 WAS VACATED ON THIS ROAD SURVEY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE SECOND ROAD EXTENDS EAST ON THE SECTION LINE TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 4-17-10 TO COMMENCE THE THIRD ROAD ON THIS ROAD SURVEY
 - 2) THE SECOND ROAD EXTENDS SOUTH ON THE SECTION LINE FOR 1,316-1/2' TO INTERSECT THE ALMA ROAD AND THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 122, A ROAD SURVEY RECORDED IN SURVEY RECORD BOOK "E" ON PAGE 122 FOR A ROAD IN TOWNSHIP 17-10 DATED SEPTEMBER 16 & 17, 1885 FOR JOAB BRIDGES, PRINCIPAL PETITIONER, **APPARENTLY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 9-17-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES WITH A DEVIATION IN THE NORTHEAST 1/4 OF SECTION 8-17-10 TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-17-10 ON THE RANGE LINE AND MORRIS COUNTY LINE TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-17-10 TO BEGIN THIS ROAD SURVEY. HE NOTED THAT THERE WAS ALREADY A ROAD ESTABLISHED ON THE SECTION LINE BETWEEN SECTIONS 4 & 9.
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD 310 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 190 TO 192 PETITIONED BY JOAB BRIDGES AND OTHERS FOR THE LOCATION OF TWO ROADS AND THE VACATION OF ONE ROAD IN TOWNSHIP 17-10 [PACKET 575 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE], THAT HE SURVEYED ON SEPTEMBER 16, 1885, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 8, 1886 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON FEBRUARY 4, 1886 BY ROLAND LAKIN, COUNT CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-17-10 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY. THE ROAD **VACATED** WAS ALL OF A CERTAIN COUNTY ROAD THAT RUNS DIAGONALLY THROUGH THE NORTHEAST 1/4 OF SECTION 8-17-10 AS FOLLOWS: COMMENCING AT 47 RODS EAST OF WHERE THE KAW RESERVE LINE CROSSES THE NORTH LINE OF SECTION 8-18-10, THENCE S. 28°40' E. FOR 80 RODS, THENCE N. 88° E. FOR 48 RODS TO INTERSECT THE SECTION LINE BETWEEN SECTIONS 8 & 9 AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 8-17-10.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 366 FEET TO AN ANGLE STONE HE SET, THEN S. 54°30' W. FOR 94.7 FEET TO AN ANGLE STONE HE SET; THEN S. 80°55' W. FOR 544 FEET TO AN ANGLE STONE HE SET, THE S. 84°52' W. FOR 480 FEET TO AN ANGLE STONE HE SET AT 10 FEET SOUTH OF THE SECTION LINE, THEN NORTHWESTERLY FOR 1,165 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-17-10, THEN WEST ON THE SECTION LINES FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO END THE SECOND ROAD ON THIS ROAD SURVEY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 218 AND DATED FEBRUARY 1902, ON A SURVEY ORDERED BY THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 9-17-10 TO BEGIN THIS **PERMANENT SURVEY**.
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 59, A **PERMANENT SURVEY** FOR THE PURPOSE OF LOCATING THE CORNERS, BOUNDARIES, AND SUBDIVISIONS OF SECTION 9-17-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK AT THE REQUEST OF CHARLES WILKINSON RECORDED IN SURVEY BOOK "F" ON PAGE 138 DATED NOVEMBER 12, 1902, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 9-17-10 ON THIS **PERMANENT SURVEY**. SEE ALSO PACKED "M 133" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE

COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 98 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.95 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 9-17-10 THAT WAS "SET BY UNKNOWN PARTIES"
 - 2) 40.02 CHAINS SOUTH TO THE 18" X 12" X 4" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 9-17-10, IN LINE WITH A HEDGE EXTENDING WEST BY THE AFFIDAVIT OF KEARNEY BRIDGES
 - 3) 80.04 CHAINS SOUTH TO THE 1" SQUARE IRON PIN HE DROVE IN A STONE LEDGE FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 9-17-10
 - 4) 20.10-1/2 CHAINS EAST TO THE 18" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 9-17-10
 - 5) 40.21 CHAINS EAST TO THE GOVERNMENT STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-17-10
 - 6) 60.33 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 9-17-10 THAT WAS SET BY MILLIKEN
 - 7) 80.42 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-10
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 26, 2002, FOR PROJECT NUMBER 02264-02, SAID THAT HE CONSIDERED THAT THE NORTHWEST CORNER OF SECTION 9-17-10 WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHWEST CORNER OF SECTION 9-17-10 FROM A RETRACEMENT OF A PERMANENT SURVEY BY ALVA J. SMITH IN 1902 RECORDED IN SURVEY BOOK "F" ON PAGE 138; I.E., ON LINE AND AT DOUBLE THE DISTANCE FROM THE NORTH 1/4 CORNER OF SECTION 9-17-10 TO THE NNW 1/16 CORNER OF SECTION 9-17-10.
- 1) 34.8' SE TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
 - 2) 46.8' SSW TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
 - 3) 92.9' WNW TO THE TOP OF A FENCE POST
 - 4) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE EAST
 - 5) 24.5' NORTH TO A LINE OF FENCE EAST-WEST
 - 6) 26.5' EAST TO A LINE OF FENCE TO THE SOUTH
 - 7) 18.0' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 23, 2006, FOR PROJECT NUMBER 06291-02 TO ESTABLISH CONTROL POINTS ON THE NORTH LINE OF SECTION 8-17-10 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 06-KS, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 8-17-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED JULY 2002.
- 1) 38.50' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 101.50' NE TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 92.9' WNW TO A CONCRETE NAIL & SHINER IN THE NEAR TOP OF A FENCE POST
 - 4) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE EAST
 - 5) 4.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH EXTENDED
 - 6) 35.0' EAST TO A LINE OF FENCE TO THE SOUTH
 - 7) 61.54' WEST TO A CAPPED 1/2" REBAR HE SET ON THIS SURVEY
 - 8) 21.10' SW TO THE TOP CENTER OF THE WEST END OF A STEEL CASING
- HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 61.65' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
 - 2) 471.54' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
 - 3) 5,281.64' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-10
- 10) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 19, 2008 FOR PROJECT NUMBER 08066-02 FOR A SURVEY OF 2 TRACTS FOR RIGHT-OF-WAY IN THE NORTHEAST 1/4 OF SECTION 8-17-10 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 06-KS, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 8-17-10 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED AUGUST 2006.
- 1) 38.50' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 101.50' NE TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 92.9' WNW TO A CONCRETE NAIL & WASHER NEAR THE TOP OF A FENCE POST
 - 4) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE EAST
 - 5) 4.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "C" TO THE SOUTH
 - 6) 35.0' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
 - 7) 61.54' WEST TO A 1/2" REBAR WITH "GEOTECH" CAP
 - 8) 21.10' SW TO THE TO CENTER OF THE WEST END OF A STEEL CASING
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 61.65' WEST TO THE 1/2" REBAR WITH "LS 752" CAP HE FOUND AT A P.O.T.
 - 2) 471.54' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT A P.O.T.
 - 3) 5,281.64' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-10
 - 4) 5,281.97' SOUTH TO THE 1" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-17-10 FROM ALVA J. SMITH
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2010 FOR PROJECT NUMBER 10053-02, A SURVEY OF THE SOUTHEAST 1/4 OF SECTION 8-17-10 FOR DON DIX, SURVEY F08003 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 8-17-10 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 34.7' SW TO A 5/8" REBAR WITH A LYON COUNTY CAP [R/W]
 - 2) 38.55' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 3) 23.5' SOUTH TO A FENCE EAST-WEST
 - 4) 4' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 300 TO THE EAST
 - 5) 4' EAST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "C" NORTH-SOUTH
 - 6) 101.50' NE TO A 40 D NAIL & WASHER IN A POWER POLE
 - 7) 92.90' WNW TO A CONCRETE NAIL & SHINER NEAR THE TOP OF A FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640.70' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 8-17-10
 - 2) 5,281.40' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 8-17-10
 - 3) 2,640.72' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 8-17-10

HIS INFORMATION IS CONTINUED ON PAGE 5

- 4) 5,281.44' SOUTH TO THE 1" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 8-17-10 FROM ALVA J. SMITH'S PERMANENT SURVEY

NORTHWEST CORNER 09-17-10