

NORTH 1/4 CORNER SECTION 11, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 152 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.88 CHAINS WEST TO THE 30" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11
 - 2) 39.87 CHAINS EAST TO THE 36" X 15" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12

- 2) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS REA PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 9 GIVES THE FOLLOWING TIES TO A PIN THAT WAS FOUND OR SET UNDER “SOUTH 1/4 CORNER SECTION 2-17-10”:
 - 1) PIN 1' NORTH OF HEDGE ON THE NORTH SIDE OF THE ROAD AND IN LINE WITH THE HEDGE RUNNING NORTH 24' SOUTH TO CORNER
 - 2) ROAD HERE IS 44' BETWEEN FENCES

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE “SW CORNER SE1/4 SECTION 2-17-10”. **MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS REA PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR**
 - 1) 24' NORTH TO A WITNESS [REA]

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2012 FOR PROJECT NUMBER 12080-02, A SURVEY OF THE EAST AND WEST HALF OF THE SOUTHWEST QUARTER OF SECTION 11-17-10 FOR DON KILTAU, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE DEEMED THAT THE NORTH 1/4 CORNER OF SECTION 11-17-10 WAS **LOST**. HE RESET THIS CORNER ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 11-17-10. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 11-17-10.
 - 1) 14.0' EAST TO A LINE OF HEDGE TO THE SOUTH
 - 2) 30.0' NNE TO A CONCRETE NAIL & BOTTLECAP IN THE EAST FACE OF A CORNER FENCE POST
 - 3) 27.3' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A BRACE POST
 - 4) 1.5' SOUTH TO THE CENTERLINE OF TRAVELED WAY OF COUNTY ROAD 300 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,637.29' WEST TO THE 1" PIN HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 11-17-10
 - 2) 2,637.29' EAST TO THE 5/8" IRON PIN WITH LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 11-17-10
 - 3) 2,638.53' SOUTH TO THE 5/8" X 24" REBAR WITH LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 11-17-10
 - 4) 5,285.93' SOUTH TO THE 5/8" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 11-17-10

NORTH QUARTER CORNER 11-17-10