

WEST 1/4 CORNER SECTION 11, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 151 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 11-17-10.
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 12 AND DATED JUNE 1882, DOES NOT MENTION THE WEST 1/4 CORNER OF SECTION 11-17-10 ON THIS ROAD SURVEY AS HE ONLY RECORDED THE CORNERS AT THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 11-17-10.
- 3) **REA PIN—MUST VERIFY AND CHECK FOR OTHER MONUMENTS BEFORE USING; THIS IRON PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY! SEE R.E.A. BOOKS 30 & 31. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' EAST TO A WITNESS
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE “SW CORNER NW1/4 SECTION 11-17-10. **VERIFY AND CHECK FOR OTHER MONUMENTS BEFORE USING; THIS IRON PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY! SEE R.E.A. BOOKS 30 & 31. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' EAST TO A WITNESS [REA]
- 5) COMMISSIONER'S ROAD JOURNAL BOOK “B”, PAGE 148

ON MAY 14, 1964 A PETITION SIGNED BY MRS. ELLEN R. HARDER AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-10 WAS PRESENTED TO W. A. STOLFUS, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON JUNE 12, 1964 RECOMMENDING THAT THE FOLLOWING ROAD BE **VACATED**:

 - 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 10-17-10 AND RUNNING SOUTH FOR 1/2 MILE AND THERE ENDING.
- 6) COMMISSIONER'S ROAD JOURNAL BOOK “C”, PAGE 15

ON MARCH 12, 2002, A PETITION SIGNED BY JEAN A. AND JAMES A. HOUK AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-10 WAS PRESENTED TO THE COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON MAY 23, 2002 AND THE FINAL ORDER DATED MAY 23, 2002 ORDERED THAT THE FOLLOWING ROAD BE **VACATED**:

 - 1) BEGINNING AT THE NORTHEAST CORNER OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 10-17-10; THENCE NORTH BETWEEN SECTIONS 10 AND 11 A DISTANCE OF ONE-QUARTER OF A MILE TO THE EAST QUARTER CORNER OF SAID SECTION 10 TO THAT PORTION OF ROAD “E” VACATED JUNE 1964 ACCORDING TO COMMISSIONERS ROAD JOURNAL BOOK “B”, PAGE 148, AND THERE ENDING.
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2012 FOR PROJECT NUMBER 12080-02, A SURVEY OF THE EAST AND WEST HALF OF THE SOUTHWEST QUARTER OF SECTION 11-17-10 FOR DON KILTAU, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE SEARCHED FOR THE STONE AND WITNESS PINS OF RECORD AT THE WEST 1/4 CORNER OF SECTION 11-17-10, BUT **NOTHING** WAS FOUND. HE DEEMED THAT THIS CORNER WAS **LOST** AND HE RESET THIS CORNER ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST

CORNERS OF SECTION 11-17-10. **HE SET A 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 11-17-10.

- 1) 7.2' SE TO A CONCRETE NAIL & WASHER IN THE NORTH SIDE OF A GATE POST
- 2) 5.7' SW TO A CONCRETE NAIL & WASHER IN THE NORTH SIDE OF A GATE POST
- 3) 22,15' WSW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 4) 4' SOUTH TO A LINE OF FENCE EAST-WEST
- 5) IN LINE WITH A STONE POST TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645.24' NORTH TO THE 1" IRON PIN HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 11-17-10
- 2) 2,645.24' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 11-17-10
- 3) 1,321.93' EAST TO THE 1/2" X 24" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 11-17-10
- 4) 2,643.86' EAST TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 11-17-10
- 5) 5,287.64' EAST TO THE CONCRETE NAIL & WASHER WITH A LYON COUNTY CAP HE SET IN A DRILL HOLE HE MADE FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 11-17-10

WEST QUARTER CORNER 11-17-10