

WEST 1/4 CORNER SECTION 12, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 148 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 12-17-10.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2012 FOR PROJECT NUMBER 12080-02, A SURVEY OF THE EAST AND WEST HALF OF THE SOUTHWEST QUARTER OF SECTION 11-17-10 FOR DON KILTAU, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE DEEMED THAT THE EAST 1/4 CORNER OF SECTION 11-17-10 WAS **OBLITERATED**. HE RESET THIS CORNER BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER AND THE ROAD RECORDS. **HE SET A DRILL HOLE WITH A CONCRETE NAIL & WASHER WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 11-17-10.
 - 1) 43.00' EAST TO A LINE OF FENCE NORTH-SOUTH
 - 2) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH
 - 3) 79.46' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) IN LINE WITH A FENCE TO THE EAST EXTENDED
 - 5) IN LINE WITH A FENCE TO THE WEST EXTENDED
 - 6) 2,631.63' NORTH TO A 5/8" IRON PIN WITH LYON COUNTY CAP FOUND [NORTHEAST CORNER OF SECTION 11]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,643.78' WEST TO THE 5/8" X 24" IRON PIN WITH LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 11-17-10
 - 2) 3,965.71' WEST TO THE 1/2" X 24" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 11-17-10
 - 3) 5,287.64' WEST TO THE 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 11-7-10

WEST QUARTER CORNER 12-17-10