

NORTH 1/4 CORNER SECTION 13, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 148 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.93 CHAINS WEST TO THE 24" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14
 - 2) 39.93 CHAINS EAST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 17, 13 & 18 ON THE RANGE LINE

- 2) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY!** REA BOOK 30 ON PAGE 18 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 13-17-10 AT 2,638.7 FEET WEST OF THE NORTHEAST CORNER OF SECTION 13-17-10 AND IN LINE WITH A FENCE TO THE NORTH AND OLD HEDGE STUMPS TO THE SOUTH.
 - 1) 23' NORTH TO A WITNESS PIN

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 12-17-10".
 - 1) 23' NORTH TO A WITNESS [REA]

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 9, 2006, FOR PROJECT NUMBER 06201-02 FOR A SURVEY OF THE SOUTHWEST 1/4 OF SECTION 13-17-10 FOR DOLD/BOYCE, SURVEY F13001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 13-17-10, BUT HE DID **NOT** FIND THE STONE. HE ACCEPTED AI CHAMNESS REA SURVEY POSITION THAT WAS MONUMENTED BY A SQUARE 5/8" REBAR FOR THE NORTH 1/4 CORNER OF SECTION 13-17-10.
 - 1) 33.2' SOUTH TO THE NEAR FACE OF A 5" PIPE FENCE POST
 - 2) 30.5' NORTH TO THE NEAR FACE OF A 5" PIPE CORNER FENCE POST
 - 3) 35.3' NE TO THE NEAR FACE OF A 5" PIPE GATE POST
 - 4) 36.1' NW TO THE NEAR FACE OF A 5" PIPE GATE POST
 - 5) IN LINE WITH A FENCE TO THE NORTH AND SOUTH [EXTENDED]
 - 6) 3.0' NORTH TO THE TRAVELED WAY GRAVEL COUNTY ROAD 290HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.85' SOUTH TO THE 5/8" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 13-17-10
 - 2) 5,288.81' SOUTH TO THE 3/4" SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 13-17-10 FROM AI CHAMNESS

NORTH QUARTER CORNER 13-17-10