

NORTH 1/4 CORNER SECTION 14, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 151 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 10" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 14-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.04 CHAINS WEST TO THE 30" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15
 - 2) 40.05 CHAINS EAST TO THE 24" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14

- 2) IN A FIELD BOOK LABELED "1952-1955" IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE FOR THE ALIGNMENT OF THE DUNLAP ROAD ON PAGE 33 IT SHOWS AN **IRON PIN ABOUT 8 FEET SOUTH OF THE CENTER OF THIS ROAD SURVEY** AT THE NORTH 1/4 CORNER OF SECTION 14-17-10 DATED OCTOBER 1953.
 - 1) 26.9' TO THE WEST GATE POST
 - 2) 15.3' TO A CORNER FENCE POST

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2012 FOR PROJECT NUMBER 12080-02, A SURVEY OF THE EAST AND WEST HALF OF THE SOUTHWEST QUARTER OF SECTION 11-17-10 FOR DON KILTAU, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND A 5/8" IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 11-17-10 FROM EXISTING REFERENCE TIES AT THE LYON COUNTY ENGINEER'S OFFICE PER TIES IN THE FIELD BOOK LABELED "1952-1955", CORNER DATED 1953.
 - 1) 44.10' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A CORNER FENCE POST
 - 2) 46.20' NE TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A BRACE POST
 - 3) IN LINE WITH A FENCE TO THE NORTH
 - 4) IN LINE WITH A FENCE TO THE SOUTH
 - 5) 6.5' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 290 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,325.19' WEST TO THE 1/2" X 24" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 11-17-10
 - 2) 2,650.38' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 11-17-10
 - 3) 2,647.40' NORTH TO THE 5/8" X 24" REBAR HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 11-17-10
 - 4) 5,285.93' NORTH TO THE 5/8" X 30" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 11-17-10

NORTH QUARTER CORNER 14-17-10