

**WEST 1/4 CORNER SECTION 14, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 151 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15-17-10.
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 113 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 35 DATED JUNE 20, 1873 TO ESTABLISH THE CORNERS TO THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 15-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 14-17-10 ON THIS **PERMANENT SURVEY**.
- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 12 AND DATED JUNE 1882, DOES NOT MENTION THE WEST 1/4 CORNER OF SECTION 14-17-10 ON THIS ROAD SURVEY AS HE ONLY RECORDED THE CORNERS AT THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 14-17-10.
- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY! SEE R.E.A. BOOKS 30 & 31. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 24.33' EAST TO A WITNESS
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 SECTION 14-17-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY! SEE R.E.A. BOOKS 30 & 31. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 24.33' EAST TO A WITNESS [REA]

WEST QUARTER CORNER 14-17-10