

**WEST 1/4 CORNER SECTION 15, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 154 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 16-17-10.
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 113 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 35 DATED JUNE 20, 1873 TO ESTABLISH THE CORNERS TO THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 15-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 15-17-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,328-1/2' SOUTH TO THE 24" X 12" X 4" LIMESTONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 15-17-10
  - 2) 2,656-1/2' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 15-17-10
  
- 3) REA BOOK 30 ON PAGE 16 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 15-17-10 AT 2,644.65 FEET SOUTH OF THE NORTHWEST CORNER OF SECTION 15-17-10, AND 2,660.65 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 15-17-10, AND ON LINE WITH HEDGES AND FENCES EAST AND WEST. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST "HEELED—IN" FOR UTILITY USE ONLY!**  
**WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 20' WEST TO A WITNESS PIN

WEST QUARTER CORNER 15-17-10