

CENTER CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A SURVEY RECORDED IN VOLUME 41 ON PAGE 603 IN THE REGISTER OF DEEDS OFFICE THAT WAS FILED FOR RECORD ON NOVEMBER 20, 1889 AND RECORDED ON APRIL 29, 1890 AND SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 18-17-10, SAID THAT **HE SET A LIMESTONE 32" X 12" X 5" MARKED WITH A PLUS ("+") NEAR THE BOTTOM ON THE WEST SIDE AND MARKED WITH A PLUS ("+") ON THE TOP** FOR THE CENTER CORNER OF SECTION 18-17-10 ON LINE BETWEEN THE NORTH AND SOUTH 1/4 CORNERS OF SECTION 18-17-10, AND AT EQUAL DISTANCE FROM EACH. HE PLACED THE CENTER CORNER IN THIS WAY BECAUSE THE WEST 1/4 CORNER OF SECTION 18-17-10 AND THE SOUTHWEST CORNER OF SECTION 18-17-10, BOTH CORNERS ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE, COULD NOT BE FOUND, AND IT IS SHOWN BY SURVEYS NUMBER 47 & 93 THAT THE 1/4 CORNER ON THE NORTH AND SOUTH SIDES OF SAID SECTION 18-17-10 WERE IN A STRAIGHT LINE BETWEEN THESE SECTION CORNERS.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,634' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-17-10
 - 2) 2,634' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 18-17-10

- 2) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 135, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 216 DATED DECEMBER 5, 1905 ORDERED BY ARTHUR PEYTON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF A TRACT OF LAND DESCRIBED AS FOLLOWS: TO WIT, THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 18-17-10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE CENTER CORNER OF SECTION 18-17-10 AT THE CORNER OF AN EAST-WEST-SOUTH FENCE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 190 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 103" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.33 CHAINS WEST TO THE STONE MARKED "1/8" HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10, FROM WHICH A SPRING BEARS S. 51-1/2° E. AT 1.40 CHAINS
 - 2) 39.14 CHAINS WEST TO THE IRON PIN HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE, FROM WHICH THE NORTHWEST CORNER OF A STONE POST BEARS S. 87° E. AT 0.30 CHAINS

- 3) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 92 BY NOTICE FROM DAVID WATERS TO PERMANENTLY ESTABLISH THE WEST LINE OF SECTIONS 18 & 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST ON THE MORRIS COUNTY LINE SAID THAT **HE SET A STAKE** FOR THE PERMANENT CENTER CORNER OF SECTION 18-17-10 BY RUNNING RIGHT LINES FROM THE CENTER POINT TO THE OPPOSITE POINT ON EACH SIDE ON THIS **PERMANENT SURVEY**. HE NOTED THAT **HE FOUND A STONE ABOUT 7 FEET NORTH AND 1-1/2 FEET WEST OF THE STAKE THAT HE SET**. THE FIELD SURVEY WAS ON APRIL 14 & 15, 1915.

CENTER CORNER 18-17-10