

CENTER CORNER OF NORTHWEST 1/4 SECTION 18, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) S. K. McCrary, Deputy County Surveyor, in Survey Number 135, a **PERMANENT SURVEY** recorded in Survey Book "F" on page 216 dated December 5, 1905 ordered by Arthur Peyton for the purpose of locating and permanently establishing the corners and boundaries of a tract of land described as follows: to wit, the southwest 1/4 of the northwest 1/4 of section 18-17-10, and run such lines as may be necessary to properly complete the work, said that **HE SET A STONE MARKED "1/8"** for the permanent center corner of the northwest 1/4 of section 18-17-10 on this **PERMANENT SURVEY**. He set this corner on line and halfway between the stone that he set for the permanent south 1/8th corner of the northwest 1/4 of section 18-17-10 and the stone that he set for the permanent north 1/8th corner of the northwest 1/4 of section 18-18-10. His field notes are in Book 2 on page 190 in the "Kretsinger Collection" of field books, and there is additional information in packet "M 103" in miscellaneous drawer number 5 in the vault in the County Engineer's Office.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.00 chains north to the stone marked "1/8" he set for the permanent north 1/8th corner of the NW1/4 of section 18-17-10, from which the east tree in a hedge fence bears N. 15-1/2° E. at 0.45 chains
 - 2) 20.00 chains south to the stone marked "1/8" he set for the permanent south 1/8th corner of the NW1/4 of section 18-17-10, from which a spring bears S. 51-1/2° E. at 1.40 chains
- 2) W. G. Ruggles, County Engineer from 1915 to 1928, in large survey SR #18001 in the survey drawer for township 17-10, shows a **HEDGE STAKE** at the center corner of the northwest 1/4 of section 18-17-10.

CENTER CORNER NORTHWEST QUARTER 18-17-10