

NORTHWEST CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 36 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 13" X 3"** FOR THE CORNER TO SECTIONS 7 & 18-17-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 38.25 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7, 8, 17 & 18-17-10
 - 2) 78.25 CHAINS EAST TO THE 18" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-17-10
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 18-17-10
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-10
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 149 DATED MARCH 23, 1877, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO END THIS PORTION OF THIS ROAD SURVEY. THIS PORTION OF THIS ROAD SURVEY EXTENDED EAST FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 18-17-10.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 119 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 62 TO 64 PETITIONED BY J. A. STANLEY AND OTHERS FOR A COUNTY ROAD ON THE LYON/MORRIS COUNTY LINE BETWEEN TOWNSHIPS 17-9 AND 17-10 [PACKET 380 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 23, 1878, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** AT THE CROSSING OF THE NEOSHO RIVER [IN SECTION 25-17-9] WHERE IT WILL BE 100 FEET WIDE, ON JULY 8, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 13, 1881 BY WILLIAM F. EWING, LYON COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY ON THE COUNTY LINE.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS SOUTH ON THE COUNTY LINE TO THE SOUTHWEST CORNER OF SECTION 19-17-10; THEN EXTENDS WEST ON THE SECTION LINE INTO CHASE COUNTY FOR 1,320 FEET; THEN EXTENDS SOUTH ON THE 1/4/4 SECTION LINE FOR 2,640 FEET [SURVEY NOTE CALLS FOR 5,280 FEET]; THEN EXTENDS EAST ON THE 1/2 SECTION LINE FOR 1,320 FEET TO THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 30-17-10 ON THE COUNTY LINE; THEN EXTENDS SOUTH ON THE COUNTY LINE TO THE SOUTHWEST CORNER OF SECTION 31-17-10 AT THE TOWNSHIP CORNER TO COMMENCE THIS ROAD SURVEY
 - 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 446 & 447 FOR ROAD NUMBER 215 ON A PETITION BY E. BARCLAY [PACKET 458 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JULY 1883, SAID THAT **HE FOUND THE STONE** AT THE *SOUTHEAST* CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND LYON AND MORRIS COUNTY LINE TO BEGIN THIS ROAD SURVEY ON THE LYON AND MORRIS COUNTY LINE. **[NOTE:** THE ORIGINAL PAPERS IN

PACKET 458 SAID THAT THEY BEGAN THIS ROAD SURVEY AT THE *NORTHWEST* CORNER OF SECTION 18-17-10 AS SHOWN ON THE DRAWING ON PAGE 447 – WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR]

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK “F” ON PAGE 55 DATED MAY 29 THROUGH JUNE 1, 1883 FOR A ROAD IN TOWNSHIPS 17 & 16, RANGE 10 FOR E. BARCLAY, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO BEGIN THIS ROAD SURVEY.

- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 215 RECORDED IN ROAD RECORD BOOK “B” ON PAGES 446 TO 448 PETITION BY E. BARCLAY AND OTHERS FOR A ROAD ON THE LYON AND MORRIS COUNTY LINE BETWEEN TOWNSHIPS 16-10 AND 17-10 [PACKET 458 IN THE VAULT IN THE COUNTY SURVEYOR’S OFFICE] THAT HE SURVEYED ON MAY 28 AND JUNE 1, 1883, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD FROM THE BEGINNING, WHICH IS THE NORTHWEST CORNER OF SECTION 18-17-10, TO THE FOOT OF THE HILL WHERE AN ANGLE IS MADE NEAR THE WEST LINE OF THE NORTHWEST 1/4 OF SECTION 30-16-10, AND IT IS 40 FEET WIDE FROM THERE TO THE TERMINUS OF THIS ROAD SURVEY, AS NOTED BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO BEGIN THIS ROAD SURVEY ON THE LYON AND MORRIS COUNTY LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 2 MILES AND 154-1/2 RODS TO AN ANGLE STONE MARKED “R+” HE SET TO BEGIN NUMEROUS ANGLES AND INTERSECTS THE COUNTY LINE AT THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 19-16-10; THEN CONTINUES NORTH ON THE COUNTY LINE FOR 3/4 OF A MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-16-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 93, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “F” ON PAGE 99 DATED JUNE 17-30, 1886 AND RECORDED IN MISCELLANEOUS VOLUME 36 ON PAGES 495 & 496 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886, TO ESTABLISH THE MISSING CORNERS AND SUBDIVIDE SECTION 7-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 7-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 24.32’ NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 18” X 11” X 4” PROPERTY STONE MARKED “60” HE SET ON THIS SURVEY
 - 2) 39.76 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 18” X 12” X 4” STONE MARKED “1/4” ON THE WEST FACE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 7-17-10
 - 3) 79.52 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 15” X 12” X 2” STONE WITH 1 NOTCH ON THE EAST EDGE AND 5 NOTCHES ON THE SOUTH EDGE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 7-17-10
 - 4) 159.05 CHAINS NORTH ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-10
 - 5) 39.12 CHAINS EAST TO THE ORIGINAL GOVERNMENT STONE HE FOUND LAYING LOOSE ON THE GROUND, AND **HE REMARKED** THE STONE ON THE

OTHER END AND OPPOSITE SIDE OF THE STONE – MARK FACES NORTH – AND **HE RESET** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 7-17-10

- 6) 59.12 CHAINS EAST TO THE 18" X 9" X 6" STONE MARKED "1/8" ON THE NORTH FACE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 7-17-10
- 7) 79.12 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-10
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 34, A JOINT **PERMANENT SURVEY** WITH THE MORRIS COUNTY SURVEYOR TO PERMANENTLY ESTABLISH THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE RECORDED IN SURVEY BOOK "E" ON PAGE 215 DATED NOVEMBER 11, 1901, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE AS HE RAN THE COUNTY LINE FROM THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF 7-17-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-10 ON THIS **PERMANENT SURVEY**.
- 9) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 135, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 216 DATED DECEMBER 5, 1905 ORDERED BY ARTHUR PEYTON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF A TRACT OF LAND DESCRIBED AS FOLLOWS: TO WIT, THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 18-17-10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 190 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 103" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
 - 1) THE CORNER OF THE CEMETERY STONE WALL BEARS S. 44-1/2° W. AT 0.53 CHAINS DISTANCE
 - 2) THE NORTHEAST CORNER OF A STONE HITCHING POST BEARS S. 56° W. AT 51 CHAINS DISTANCE
 - 3) THE SOUTHEAST CORNER OF A STONE FENCE POST BEARS N. 40-1/2° W. AT 0.3 CHAINS DISTANCE

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 20.01 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10, THAT IS **10-1/2 LINKS WEST** OF THE TRUE LINE FROM THE NORTHWEST CORNER OF SECTION 18-17-10 TO THE WEST 1/4 CORNER OF SECTION 18-17-10
 - 2) 40.02 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE IRON PIN HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 18-17-10, FROM WHICH THE NORTHWEST CORNER OF A STONE POST BEARS S. 87° E. AT 0.30 CHAINS
 - 3) 18.82 CHAINS EAST TO THE STONE MARKED "1/8" HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10, FROM WHICH THE EAST TREE IN A HEDGE FENCE BEARS N. 15-1/2° E. AT 0.45 CHAINS
 - 4) 39.44 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-17-10, AT 0.36-1/2 CHAINS FROM THE NORTH FENCE AND 0.31 CHAINS FROM THE SOUTH FENCE

CONTINUED ON PAGE 4

- 10) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,323' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 18-17-10
 - 2) 2,646' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 18-17-10
 - 3) 5,292' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF SECTION 18-17-10
- 11) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 92 BY NOTICE FROM DAVID WATERS TO PERMANENTLY ESTABLISH THE WEST LINE OF SECTIONS 18 & 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST ON THE MORRIS COUNTY LINE SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON APRIL 14 & 15, 1915. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,323' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SEC. 18-17-10
 - 2) 2,646' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-10
 - 3) 5,292' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 18-18-10
 - 4) 7,938' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10
 - 5) 10,584' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-17-10
- 11) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 68
ON NOVEMBER 28, 1950 A PETITION SIGNED BY J. M. MILLER AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-10 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND R. W. BALL, COUNTY ENGINEER, ON JANUARY 5, 1951 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 8, 1951 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING ON THE NORTHWEST CORNER OF SECTION 18-17-10, THENCE SOUTH ALONG THE COUNTY LINE BETWEEN LYON AND MORRIS COUNTIES TO A COUNTY ROAD WHICH RUNS NORTHWESTERLY AND SOUTHEASTERLY, A DISTANCE OF 3/4 MILE, AND ENDING THEREON.
- 12) IN A FIELD BOOK LABELED "1952-1955" IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE FOR THE ALIGNMENT OF THE DUNLAP ROAD ON PAGE 29 IT SHOWS A **STONE & 1/2" IRON PIN** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE DATED OCTOBER 1953.
- 1) 1/2" IRON PINS WERE SET 50' NW, 50' WSW AND 50' SSE
 - 2) 35.5' SW TO A STONE POST AT THE CORNER OF THE CEMETERY
- 13) IN THE SURVEY FOLDER IN THE DRAWER FOR TOWNSHIP 17-10, ON A SURVEY LABELED "SURVEY FOR SCOTT MOUSE HOCH" WITH NO NAME OR DATE, IT SHOWS A **STONE AND IRON PIN** AT THE NORTHWEST CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE.

- 1) 1/2" IRON PINS WERE SET 50' NW, 50' WSW AND 50' SSE
 - 2) 35.5' SW TO A STONE POST AT THE CORNER OF THE CEMETERY
- 14) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **STONE WITH A 1/2" SQUARE IRON PIN BY THE STONE** AT THE "NW CORNER SECTION 18-17-10" ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE.
- 1) CORNER OF STONE WALL BEARS S. 44.5° W AT 0.53 [CHAINS?]
 - 2) NE CORNER OF STONE HITCHING POST BEARS S. 56° W. AT 0.38 [CHAINS?]
 - 3) SE CORNER OF FENCE POST BEARS N. 40.5° W AT 0.38 [CHAINS?]
 - 4) 50' NW TO A 1/2" SQUARE IRON PIN
 - 5) 50' WSW TO A 1/2" SQUARE IRON PIN
 - 6) 50' SSW TO A 1/2" SQUARE IRON PIN
 - 7) 35.5' SW TO A STONE CORNER POST OF THE CEMETERY

NORTHWEST CORNER 18-17-10