

WEST 1/4 CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 36 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 24" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-17-10
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-10

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A SURVEY RECORDED IN VOLUME 41 ON PAGE 603 IN THE REGISTER OF DEEDS OFFICE THAT WAS FILED FOR RECORD ON NOVEMBER 20, 1889 AND RECORDED ON APRIL 29, 1890 AND SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 18-17-10, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS SURVEY.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 34, A JOINT **PERMANENT SURVEY** WITH THE MORRIS COUNTY SURVEYOR TO PERMANENTLY ESTABLISH THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND MORRIS COUNTY LINE RECORDED IN SURVEY BOOK "E" ON PAGE 215 DATED NOVEMBER 11, 1901, SAID THAT **HE SET A 1" GAS PIPE 12" LONG** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE, AT THE POINT OF INTERSECTION OF THE LINE BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-10 AND THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 7-17-10, AND THE EXTENSION TO THE EAST OF A LINE PASSING THROUGH THE STONE THAT HE FOUND AT THE CENTER CORNER OF SECTION 13-17-9 IN MORRIS COUNTY AND THAT STONE THAT HE FOUND AT THE SOUTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 13-17-9 ON THIS **PERMANENT SURVEY**. HE NOTED THAT LINES WERE RUN WITH A TRANSIT AND MEASUREMENTS WERE MADE WITH A STEEL TAPE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.81 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 7-17-10
 - 2) 40.03 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-10

- 4) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 135, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 216 DATED DECEMBER 5, 1905 ORDERED BY ARTHUR PEYTON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF A TRACT OF LAND DESCRIBED AS FOLLOWS: TO WIT, THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 18-17-10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND AN IRON PIN IN PLACE** AT THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**, FROM WHICH THE NORTHWEST CORNER OF A STONE POST BEARS S. 87° E. AT 0.30 CHAINS. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 190 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL

INFORMATION IN PACKET "M 103" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.01 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10, THAT IS **10-1/2 LINKS WEST** OF THE TRUE LINE FROM THE NORTHWEST CORNER OF SECTION 18-17-10 TO THE WEST 1/4 CORNER OF SECTION 18-17-10
- 2) 40.02 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 18-17-10
- 3) 18.81 CHAINS EAST TO THE STONE MARKED "1/8" HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10, FROM WHICH A SPRING BEARS S. 51-1/2° E. AT 1.40 CHAINS
- 4) 39.14 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE CENTER CORNER OF SECTION 18-17-10, IN THE CORNER OF EAST, WEST AND SOUTH FENCES

- 5) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SHOWS THAT **HE SET A STONE** FOR THE WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF SECTION 18-17-10
- 2) 1,323' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 18-17-10
- 3) 2,646' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-17-10

- 6) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 92 BY NOTICE FROM DAVID WATERS TO PERMANENTLY ESTABLISH THE WEST LINE OF SECTIONS 18 & 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST ON THE LYON AND MORRIS COUNTY LINE SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE HALFWAY BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 18-17-10 AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 18-17-10 ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON APRIL 14 & 15, 1915.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SEC. 18-17-10
- 2) 2,646' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 18-17-10
- 3) 2,646' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 18-17-10
- 4) 5,292' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10
- 5) 7,938' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-17-10

WEST QUARTER CORNER 18-17-10