

WEST 1/16 CORNER OF THE NORTHWEST 1/4 SECTION 18, TOWNSHIP 17 SOUTH, RANGE 10 EAST

1) S. K. McCrary, Deputy County Surveyor, in Survey Number 135, a **PERMANENT SURVEY** recorded in Survey Book "F" on page 216 dated December 5, 1905 ordered by Arthur Peyton for the purpose of locating and permanently establishing the corners and boundaries of a tract of land described as follows: to wit, the southwest 1/4 of the northwest 1/4 of section 18-17-10, and run such lines as may be necessary to properly complete the work, said that **HE FOUND THE STONE IN PLACE** at the west 1/8th corner of the northwest 1/4 of section 18-17-10 on the range line and the Lyon and Morris County line, that is halfway between the northwest corner of section 18-17-10 and the west 1/4 corner of section 18-17-10 and **10-1/2 links west** of a true line between these corners on this **PERMANENT SURVEY**. His field notes are in Book 2 on page 190 in the "Kretsinger Collection" of field books, and there is additional information in packet "M 103" in miscellaneous drawer number 5 in the vault in the County Engineer's office.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.01 chains north on the range line and county line to the stone he found in place at the northwest corner of section 18-17-10
- 2) 20.01 chains south on the range line and county line to the iron pin he found in place at the west 1/4 corner of section 18-17-10, from which the northwest corner of a stone post bears S. 87° E. at 0.30 chains

2) W. S. Ruggles, County Engineer from 1915 to 1928, in large survey SR #18001 in the survey drawer for township 17-10, shows that **HE FOUND THE STONE** at the west 1/8th corner of the northwest 1/4 of section 18-17-10 on the range line and the Lyon and Morris County line on this survey.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' north on the range line and county line to the stone he found at the northwest corner of section 18-17-10
- 2) 1,323' south on the range line and county line to the stone he set for the west 1/4 corner of section 18-17-10
- 3) 3,969' south on the range line and county line to the stone he set for the southwest corner of section 18-17-10

3) W. S. Ruggles, County Engineer from 1915 to 1928, in a **PERMANENT SURVEY** recorded in permanent survey book 1 on page 92 by notice from David Waters to permanently establish the west line of sections 18 & 19, township 17 south, range 10 east on the Morris County line said that **HE FOUND THE STONE IN PLACE** at the west 1/8th corner of the northwest 1/4 of section 18-17-10 on the range line and the Lyon and Morris County line on this **PERMANENT SURVEY**. The field survey was on April 14 & 15, 1915.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' north on the range line and county line to the stone he found in place at the northwest corner of section 18-17-10
- 2) 1,323' south on the range line and county line to the stone he set for the permanent west 1/4 corner of section 18-17-10
- 3) 3,969' south on the range line and county line to the stone he set for the permanent southwest corner of section 18-17-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 6,615' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10
- 5) 9,261' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-17-10

WEST SIXTEENTH CORNER NORTHWEST QUARTER 18-17-10