

CENTER CORNER SECTION 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 19-17-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,325-1/2' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 19-17-10
 - 2) 2,651' EAST TO THE STONE **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-17-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 126 DATED APRIL 12, 1882 AT THE REQUEST OF P. BOSTIAN TO SURVEY AND ESTABLISH THE 1/4 CORNER AND THE 1/8TH CORNER ON THE WEST LINE OF SECTION 19, AND THE 1/8TH CORNER BETWEEN THE CENTER CORNER AND THE 1/4 CORNER ON THE SOUTH LINE, ALL IN TOWNSHIP 17-10, AND SUCH OTHER LINES AND CORNERS AS NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.10-1/2 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SE1/4 OF SECTION 19-17-10
 - 2) 40.21 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 124 DATED SEPTEMBER 23 & 24, 1885 ORDERED BY HIRAM DRIGGS TO LOCATE THE CENTER CORNER OF SECTION 19-17-10, SAID THAT **HE SET A LIMESTONE** FOR THE PERMANENT CENTER CORNER OF SECTION 19-17-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE CENTER 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,330' NORTH TO THE 6" X 8" X 16" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10
 - 2) 2,660' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-17-10

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 10041-02, SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO SURVEY THE SOUTH LINE OF THE NORTH HALF OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 19-17-10 FOR DAVID GROTHOR, SAID THAT HE SEARCHED FOR THE STONE AT THE

CENTER CORNER OF SECTION 19-17-10, BUT THE STONE WAS **NOT** FOUND. HE CONSIDERED THAT THIS CORNER WAS **LOST** IN NORTH-SOUTH POSITION AND HE RESET IT ON TRUE LINE BETWEEN THE STONES THAT HE FOUND AT THE WEST QUARTER CORNER AND THE EAST QUARTER CORNER OF SECTION 19-17-10. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED** IN EAST-WEST POSITION AND HE USED THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER FOR EAST-WEST POSITION. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 19-17-10.

- 1) 2.35' NORTH TO A SPIKE & BOTTLE CAP IN A 30" TREE
- 2) 1.20' SOUTH TO A HEDGE CORNER POST
- 3) IN A LINE OF TREES NORTH & SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,550.33' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
- 2) 1,331.35' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 1,330']
- 3) 2,662.69' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 2,660']
- 4) 2,646.32' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-17-10

CENTER CORNER 19-17-10