

**NORTH 1/4 CORNER SECTION 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 164 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-17-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 38.75 CHAINS WEST TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 18, 19 & 24 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  - 2) 40.00 CHAINS EAST TO THE 20" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 5,312' SOUTH TO THE 16" X 12" X 6" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-17-10
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 124 DATED SEPTEMBER 23 & 24, 1885 ORDERED BY HIRAM DRIGGS TO LOCATE THE CENTER CORNER OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.
  
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A SURVEY RECORDED IN VOLUME 41 ON PAGE 603 IN THE REGISTER OF DEEDS OFFICE THAT WAS FILED FOR RECORD ON NOVEMBER 20, 1889 AND RECORDED ON APRIL 29, 1890 AND SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 18-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 18-17-10 ON THIS SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,634' NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SEC. 18-17-10
  - 2) 5,268' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-17-10
  
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,330' SOUTH TO THE 6" X 8" X 16" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10
  - 2) 2,660' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 19-17-10
  
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 10041-02,

SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO SURVEY THE SOUTH LINE OF THE NORTH HALF OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 19-17-10 FOR DAVID GROTH, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 19-17-10 WITH A COUNTY BACKHOE, BUT **NO** STONE WAS FOUND. HE CONSIDERED THAT THIS CORNER WAS BOTH **LOST** AND **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP FOR THE NORTH 1/4 CORNER OF SECTION 19-17-10 ON TRUE LINE BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 19-17-10 AND IN LINE WITH PHYSICAL EVIDENCE TO THE NORTH AND SOUTH.**

- 1) 24.0' SW TO THE SOUTHWEST CORNER TO THE EDGE OF WEARING SURFACE
  - 2) 30.8' NW TO THE NORTHWEST CORNER OF THE EDGE OF WEARING SURFACE
  - 3) 12.7' WEST TO THE EDGE OF THE WEARING SURFACE
  - 4) IN LINE WITH A FENCE TO THE NORTH EXTENDED
  - 5) 9' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 280 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,557.49' WEST TO THE STONE AND REBARS HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 19-17-10 ON THE RANGE LINE AND LYON AND MORRIS COUNTY LINE
  - 2) 2,643.77' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 19-17-10
  - 3) 1,331.34' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10
  - 4) 2,662.69' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 19-17-10

NORTH QUARTER CORNER 19-17-10