

WEST 1/4 CORNER SECTION 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 36 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 4"** FOR THE WEST 1/4 CORNER OF SECTION 19-17-10 ON THE WEST TOWNSHIP BOUNDRY AND THE COUNTY LINE.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-10
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-17-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 126 DATED APRIL 12, 1882 AT THE REQUEST OF P. BOSTIAN TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE 1/4 CORNER AND THE 1/8TH CORNER ON THE WEST LINE OF SECTION 19 AND THE 1/8TH CORNER BETWEEN THE CENTER CORNER AND THE 1/4 CORNER ON THE SOUTH LINE, AND SUCH OTHER LINES AND CORNERS AS NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-17-10 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 20.05 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 19-17-10
 - 2) 40.10 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-17-10
 - 3) 20.05 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 19-17-10
 - 4) 40.10 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-17-10
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 124 DATED SEPTEMBER 23 & 24, 1885 ORDERED BY HIRAM DRIGGS TO LOCATE THE CENTER CORNER OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.
- 5) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SHOWS THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 19-17-10
- 2) 2,646' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-17-10

- 6) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 92 BY NOTICE FROM DAVID WATERS TO PERMANENTLY ESTABLISH THE WEST LINE OF SECTIONS 18 & 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST ON THE LYON AND MORRIS COUNTY LINE SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE AT HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 19-17-10 AND THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-17-10 THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON APRIL 14 & 15, 1915.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-17-10
- 2) 2,646' NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 19-17-10
- 3) 5,292' NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-10
- 4) 6,615' NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SEC. 18-17-10
- 5) 7,938' NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 19-17-10

- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 9, 1985, FOR PROJECT NUMBER 85142, SURVEY F19002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A 3.0 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 19-17-10 RECORDED IN VOLUME 421 ON PAGE 158 IN THE REGISTER OF DEEDS OFFICE ON NOVEMBER 21, 1985, SAID THAT **HE FOUND A 5" X 9" LIMESTONE** AT THE WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE. THIS SURVEY IS FILED IN VOLUME 421 ON PAGE 158 IN THE REGISTER OF DEEDS OFFICE.

- 1) **HE SET 1/2" REBARS WITH HIS "LS 752" CAPS ON THE EAST AND WEST SIDES OF THE STONE**
- 2) 12.85' WNW TO THE SOUTHEAST CORNER OF A HUBGUARD
- 3) 15.5' ENE TO THE SOUTHWEST CORNER OF A HUBGUARD
- 4) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 65.0' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE #4 REBAR WITH HIS PLASTIC "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 3.0 ACRE TRACT
- 2) 265.0' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE #4 REBAR WITH HIS PLASTIC "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 3.0 ACRE TRACT
- 3) 2,645.9' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE & REBARS HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-17-10

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 10041-02, SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO SURVEY THE SOUTH LINE OF THE NORTH HALF OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 19-17-10 FOR DAVID GROTHER, SAID THAT **HE FOUND THE 5" X 9" LIMESTONE** AT THE

WEST 1/4 CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED NOVEMBER 1985.

- 1) **1/2" REBARS WITH HIS "LS 752" CAP ON THE EAST AND WEST SIDES OF THE STONE**
- 3) 54.3' NW TO A NAIL & WASHER IN A FIBER OPTIC SIGN POST
- 3) 108.3' SE TO A NAIL & WASHER IN A FIBER OPTIC SIGN POST
- 4) 12' NORTH TO THE CENTER OF A CREEK

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645.85' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 19-17-10
- 2) 2,550.33' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 19-17-10
- 3) 5,195.65' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-17-10

WEST QUARTER CORNER 19-17-10