

**WEST 1/16 CORNER OF THE NORTHEAST 1/4 SECTION 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SAID THAT **HE SET A 6" X 8" X 16" STONE** FOR THE PERMANENT SOUTHWEST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 19-17-10 ON LINE AND MIDWAY BETWEEN THE STONE HE FOUND AT THE CENTER 1/4 CORNER OF SECTION 19-17-10 AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,330' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-17-10
- 2) 1,330' SOUTH TO THE STONE HE FOUND AT THE CENTER 1/4 CORNER OF SECTION 19-17-10
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 10041-02, SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO SURVEY THE SOUTH LINE OF THE NORTH HALF OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 19-17-10 FOR DAVID GROTHOR, SAID THAT HE SEARCHED FOR THE STONE THAT WAS SET BY ALVA J. SMITH [COUNTY SURVEYOR FROM 1900 THROUGH 1906] IN 1901 IN SURVEY BOOK "E" ON PAGE 209 AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 19-17-10, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" X 30" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 19-17-10 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 19-17-10.

- 1) 8.00' NORTH TO THE SOUTHEAST CORNER OF A STONE POST AT GROUND LEVEL
- 2) 10.40' NORTH TO A SPIKE & BOTTLECAP IN A 20" HONEY LOCUST TREE
- 3) 6.00' NORTH TO A CROP LINE TO THE EAST EXTENDED
- 4) 2.00' WEST TO A TREE LINE TO THE SOUTH EXTENDED

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,331.34' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 1,330']
- 2) 1,331.35' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 1,330']
- 3) 2,645.03' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10

WEST SIXTEENTH CORNER NORTHEAST QUARTER 19-17-10