

WEST 1/16 CORNER OF THE NORTHWEST 1/4 SECTION 20, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT AFTER HE RAN THE SECTION LINES FROM THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-10 SOUTH TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-17-10, **HE RESET THE STONE THAT HE FOUND** "AT THE CORRESPONDING CORRECTION OF 1/4 AND 1/8 CORNERS ON BOTH LINES AND SET UP THE OLD OR MARKED STONES I FOUND LYING NEAR THEIR RESPECTIVE PLACES" FOR THE EAST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SAID THAT **HE SET A 5" X 10" X 18" STONE** FOR THE PERMANENT SOUTHEAST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 19-17-10 ON LINE AND MIDWAY BETWEEN THE STONES THAT HE FOUND AT THE NORTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,340' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-10
 - 2) 1,340' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 19-17-10
 - 3) 2,678' SOUTH TO THE STONE HE FOUND AT THE EAST 1/8TH CORNER ON THE EAST SIDE OF THE SE1/4 OF SECTION 19-17-10
 - 4) 4,016' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-17-10

- 3) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE LINE BETWEEN THE NORTH HALF AND THE SOUTH HALF OF THE NORTHEAST 1/4 OF SECTION 19-17-10, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 19-17-10 ON THIS SURVEY. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 2010 FOR PROJECT NUMBER 10041-02, SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO SURVEY THE SOUTH LINE OF THE NORTH HALF OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 19-17-10 FOR DAVID GROTHOR, SAID THAT HE EXCAVATED WITH A COUNTY BACKHOE FOR ALVA J. SMITH'S STONE AT THE EAST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 19-17-10. **HE FOUND THE LIMESTONE WITH THE TOP BROKEN AND HE SET A 1/2" X 24" REBAR WITH LS 752 CAP OVER THE TOP OF THE STONE** AT THE EAST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 19-17-10.
 - 1) HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE CENTER OF THE STONEHIS TIES ARE CONTINUED ON PAGE 2

- 2) HE SET A 1/2" X 30' REBAR WITH HIS "LS 752" CAP ON THE EAST SIDE CENTER OF THE STONE
- 3) 41.0' WSW TO THE NORTHEAST CORNER OF A STONE POST
- 4) 120.7' NNE TO A NAIL & ID WASHER IN THE SOUTHEAST FACE OF A FIBER OPTIC POST
- 5) 38.0' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 6) 1.0' EAST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "B" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645.03' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10
- 2) 1,340.16' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 1,340']
- 3) 1,339.81' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-17-10 [SMITH = 1,340']

WEST SIXTEENTH CORNER NORTHWEST QUARTER 20-17-10