

**WEST 1/16 CORNER OF THE SOUTHWEST 1/4 SECTION 20, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT AFTER HE RAN THE SECTION LINES FROM THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-17-10 TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-17-10, **HE RESET THE STONE** THAT HE FOUND "AT THE CORRESPONDING CORRECTION OF 1/4 AND 1/8 CORNERS ON BOTH LINES AND SET UP THE OLD OR MARKED STONES I FOUND LYING NEAR THEIR RESPECTIVE PLACES" FOR THE 1/8<sup>TH</sup> CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**.
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 125 DATED APRIL 11, 1882 AT THE REQUEST OF J. E. ROBERTS TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE CENTER CORNER OF SECTION 20 AND THE 18<sup>TH</sup> CORNER BETWEEN THE CENTER AND THE 1/4 CORNER ON THE WEST, THE 1/8<sup>TH</sup> CORNER BETWEEN THE SOUTHWEST CORNER OF THE SECTION AND THE 1/4 CORNER ON THE SOUTH, AND THE 1/16<sup>TH</sup> CORNER IN THE CENTER OF THE SOUTHWEST 1/4, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/8<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 20.11-1/2 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT 1/16<sup>TH</sup> CORNER IN THE CENTER OF THE SW1/4 OF SECTION 20-17-10
  - 2) 40.23 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT EAST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 20-17-10
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE EAST 1/8<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,338' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-17-10
  - 2) 1,338' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 19-17-10
  - 3) 3,678' NORTH TO THE 5" X 10" X 18" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 19-17-10
  - 4) 4,018' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-10

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 20-17-10