

WEST 1/4 CORNER SECTION 21, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 157 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 10" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 21-17-10.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 125 DATED APRIL 11, 1882 AT THE REQUEST OF J. E. ROBERTS TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE CENTER CORNER OF SECTION 20 AND THE 18TH CORNER BETWEEN THE CENTER AND THE 1/4 CORNER ON THE WEST, THE 1/8TH CORNER BETWEEN THE SOUTHWEST CORNER OF THE SECTION AND THE 1/4 CORNER ON THE SOUTH, AND THE 1/16TH CORNER IN THE CENTER OF THE SOUTHWEST 1/4, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.46 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 20-17-10

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN VOLUME 3 ON PAGE 555 IN THE REGISTER OF DEEDS OFFICE ON MAY 29, 1880 AND SURVEY F21001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO PERMANENTLY ESTABLISH THE CORNERS OF THE NORTH 1/2 OF THE NORTHWEST 1/4, AND THE NORTHEAST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4, AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, AND THE SOUTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 21-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 21-17-10 ON THIS **PERMANENT SURVEY**. HE BEGAN THIS SURVEY ON APRIL 22, 1880.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.76-1/2 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-17-10
 - 2) 19.88 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 21-17-10, AT **3 LINKS WEST OF THE LINE** BETWEEN THE STONES THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-17-10 AND THE NORTHWEST 1/4 OF SECTION 21-17-10
 - 3) 39.76-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 21-17-10

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 141, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 222 DATED JANUARY 23-30, 1906 AT THE ORDER OF JOHN GUTHRIE FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THAT PORTION OF THE SOUTHEAST 1/4 OF SECTION 17-17-10 WHICH LIES EAST OF THE EAST LINE OF THE DIMINISHED KANSAS INDIAN RESERVATION, EXCEPTING THOSE ON THE NORTH LINE, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE ON LINE WITH A FENCE AND 36 LINKS WEST OF A HEDGE** AT THE EAST 1/4 CORNER OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**. SEE BOOK "E" IN THE KRETSINGER COLLECTION ON PAGES 14 & 15, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 14" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 39.91 CHAINS NORTH TO THE PIECE OF SICKLE BAR HE DROVE IN ROCK LEDGE FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 17-17-10
 - 2) 79.82 CHAINS NORTH TO THE STONE HE FOUND IN PLACE, BUT SETTING THE WRONG WAY IN THE GROUND, AT THE EAST 1/4 CORNER OF SECTION 17-17-10 AT 53 INKS EAST OF A STONE WALL
 - 3) 119.77 CHAINS NORTH BY HIS CHAINING NOTES TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 17-17-10, AND 119.76 CHAINS SHOWN ON HIS SURVEY DRAWING
- 5) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 17 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 21-17-10 AT 2,629 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 21-17-10 AT A STONE POST AND FENCE TO THE WEST AND A HEDGE TO THE EAST ON APRIL 26, 1939. THIS LOCATION WAS 2,635.5 FEET SOUTH OF THE STONE AT THE NORTHWEST CORNER OF SECTION 21-17-10. A NOTE IN THE MARGIN SAID THAT THEY **CORRECTED** THIS LOCATION TO 2,632.25’ FROM EITHER SECTION CORNER, AND **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 21-17-10. SEE PAGE 17 FOR ADDITIONAL INFORMATION.

WEST QUARTER CORNER 21-17-10