

NORTH 1/4 CORNER SECTION 22, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 154 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-17-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.22 CHAINS WEST TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22
 - 2) 40.22 CHAINS EAST TO THE 24" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 112 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 34 DATED JUNE 19, 1873 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 15 & 22 AND FIND THE CENTER OF SECTION 22-17-10, SAID THAT **HE SET A 36" X 12" X 6" STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 22-17-10 ON LINE AND HALFWAY BETWEEN THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-178-10 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,664-1/2' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-10
 - 2) 2,664-1/2' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 113 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 35 DATED JUNE 20, 1873 TO ESTABLISH THE CORNERS TO THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 15-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-22-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 5,315' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 15-17-10

- 4) REA BOOK 30 ON PAGE 15 SAYS THAT **THEY SET AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 15-17-10 AT 2,669.15' WEST OF THE SOUTHEAST CORNER OF SECTION 15-17-10. HE NOTED THAT THERE WAS A HEDGE TO THE NORTH AT 1,333' WEST OF THE SOUTHEAST CORNER. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' SOUTH TO A WITNESS PIN

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS AN **IRON PIN** AT THE "SW CORNER SE1/4 SECTION 15-17-10". **VERIFY BEFORE USING AS THIS IS THE REA PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25' SOUTH TO A WITNESS

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 18, 1998, FOR JOB NUMBER 96320 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 96-7Q, SAID THAT **HE FOUND A SQUARE #6 REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 15-17-10.

HIS TIES ARE ON PAGE 2

- 1) 35.6' NE TO A 40 D NAIL & WASHER IN A FENCE POST
 - 2) 33.8' NW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 51.1' SE TO A 40 D NAIL & WASHER IN A FENCE POST
 - 4) 91.0' SW TO A 40 D NAIL & WASHER IN A FENCE POST
 - 5) 2,661.97' WEST TO THE NORTHWEST CORNER OF SECTION 22
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,661.97' WEST TO THE 5/8" CAPPED REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 15-17-10

NORTH QUARTER CORNER 22-17-10